GNU/Linux-libre from source code

for Core 2

Christophe Jarry

This is edition 1.9.1 (last updated November 2026) of *GNU/Linux-libre from source code for Core 2*.

Copyright © 2026 Christophe Jarry.

This document was based on the Chinese page `http://zdbr.net.cn/download/Loongson64-2.0.htm`, which was copyright © 2009 Haiyong Sun. His blog is on `http://blog.chinaunix.net/uid/436750.html`.

Various formats of this manual as well as its texinfo source are available on `http://cjarry.org/gnu-linux/gllfsc/core2/`.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Computer instructions in this manual are free software: you can redistribute them and/or modify them under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Those instructions are distributed in the hope that they will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this manual. If not, see <http://www.gnu.org/licenses/>.

Short Contents

1 Introduction 1
2 Prerequisites 5
3 Preliminary Work 7
4 Building the Cross-Compilation Toolchain 17
5 Building the Cross-Compilation Tools 25
6 Building the Target System 31
7 Creating Required Configuration Files for the New System 65
8 Before Booting GLLFSC 69
9 After Booting GLLFSC 73
10 Further Readings 93
11 Thanks 95
A GNU Free Documentation License 97
B GNU General Public License 105

Table of Contents

1 Introduction 1

1.1 GNU/Linux History 1
1.1.1 GNU 1
1.1.2 HURD 1
1.1.3 Linux 2
1.1.4 Linux-libre 2
1.1.5 References 2
1.2 Purpose of this Document 3

2 Prerequisites 5

2.1 Definitions 5
2.1.1 `sysroot` 5
2.1.2 Toolchain 5
2.1.3 `build`, `host` and `target` 5
2.1.4 FHS 6
2.2 Commands 6

3 Preliminary Work 7

3.1 Package Users Introduction 7
3.1.1 Package Installation 7
3.1.2 Package Removal 8
3.1.3 Package Information 8
3.2 Build OS 8
3.3 Tmux Usage 9
3.4 Work Directory Creation 9
3.5 Setting up Required Environment Variables 9
3.6 Build Partition Creation 11
3.7 Mounting Partition 11
3.8 Creating Compilation and Download Directories 11
3.9 Downloads 11
3.9.1 Downloading Packages 11
3.9.2 Downloading Patches 14
3.10 Final Preparations 14
3.10.1 Target Filesystem Hierarchy Creation 14
3.10.2 Target Filesystem Hierarchy Ownership 15
3.10.3 Creating needed user, groups and log files 15

4 Building the Cross-Compilation Toolchain 17

4.1 Target Linux-Headers 17
4.2 Cross Binutils 18
4.3 Cross GCC (C support only) 20
4.4 Target glibc 21
4.5 Cross GCC (C and C++ support) 24

5 Building the Cross-Compilation Tools 25

5.1 File 25

5.2 Groff 25
5.3 Shadow 25
5.4 M4 29
5.5 Ncurses 30
5.6 Cleaning up Cross-Compilation Toolchain 30

6 Building the Target System 31
6.1 Setting up the Environment 31
6.2 Automating the Build 31
6.3 Man Pages 33
6.4 Zlib 33
6.5 Binutils 34
6.6 GMP 34
6.7 MPFR 35
6.8 MPC 35
6.9 GCC 35
6.10 Sed 36
6.11 E2fsprogs 37
6.12 Coreutils 38
6.13 iana-etc 39
6.14 M4 39
6.15 Bison 40
6.16 Ncurses 40
6.17 Libtool 41
6.18 Readline 41
6.19 Autoconf 41
6.20 Automake 42
6.21 Bash 42
6.22 Bzip2 43
6.23 DHCPCD 44
6.24 Diffutils 45
6.25 File 45
6.26 Findutils 45
6.27 Flex 46
6.28 Gawk 47
6.29 Gdbm 47
6.30 Gettext 47
6.31 Grep 48
6.32 Groff 48
6.33 Gzip 49
6.34 Inetutils 49
6.35 Iproute2 50
6.36 Kbd 51
6.37 Kmod 51
6.38 Less 52
6.39 Libpipeline 52
6.40 Make 53
6.41 Man-db 53
6.42 Nano 54
6.43 Patch 54
6.44 Psmisc 55

6.45 Shadow 55
6.46 Sysvinit 56
6.47 Tar 58
6.48 Texinfo 58
6.49 Udev 59
6.50 Util-Linux 60
6.51 XZ-Utils 60
6.52 Bootscripts 61
6.53 The Kernel 61
6.54 GRUB 63

7 Creating Required Configuration Files for the New System . 65
7.1 File for Time Setup 65
7.2 Setting up Keyboard Function keys for the Shell 65
7.3 Setting up Bash Shell Startup Files 66
7.4 Localhost Setup 66
7.5 Setting up `hosts` File 66
7.6 Setting up Network Address 66
7.6.1 Setting up Network Static Address 66
7.6.2 Setting up Network Dynamic Address 67
7.7 Setting up DNS 67
7.8 `fstab` File Creation 67

8 Before Booting GLLFSC 69
8.1 Enabling Package Users on the target GLLFSC 69
8.2 Archiving the System 70
8.3 Some Recommendations 70
8.4 Halting the Computer 71

9 After Booting GLLFSC 73
9.1 Boot Process 73
9.2 Login 73
9.3 Locales 73
9.4 Libevent 74
9.5 Tmux 75
9.6 Timezone 75
9.7 Runit 76
9.8 Perl 80
9.9 OpenSSL 81
9.10 Wpa_supplicant 81
9.11 Wireless_tools 82
9.12 Wget 83
9.13 Libtasn1 83
9.14 Lynx 83
9.15 CA-Certificates 84
9.16 Procps-ng 89
9.17 Package Users Final Tweaks 89
9.18 Archiving the Complete System 91
9.19 Add User 91
9.20 Halting the Computer 92

10 Further Readings **93**

11 Thanks **95**

Appendix A GNU Free Documentation License **97**

Appendix B GNU General Public License **105**

1 Introduction

1.1 GNU/Linux History

1.1.1 GNU

GNU (GNU's Not Unix) is a project launched by Richard Stallman in 1984 with the goal of building an entirely free operating system compatible with Unix[1]. "Free" here means "free as in freedom". In this context, a free operating system is an operating system you can use and share in freedom. A core part of his motivation is given in the GNU Manifesto[2]:

> I consider that the Golden Rule requires that if I like a program I must share it with other people who like it. Software sellers want to divide the users and conquer them, making each user agree not to share with others. I refuse to break solidarity with other users in this way. I cannot in good conscience sign a nondisclosure agreement or a software license agreement. For years I worked within the Artificial Intelligence Lab to resist such tendencies and other inhospitalities, but eventually they had gone too far: I could not remain in an institution where such things are done for me against my will.
>
> So that I can continue to use computers without dishonor, I have decided to put together a sufficient body of free software so that I will be able to get along without any software that is not free. I have resigned from the AI Lab to deny MIT any legal excuse to prevent me from giving GNU away.

A program is free software if the program's user has the four essential freedoms:

- The freedom to run the program, for any purpose (freedom 0).
- The freedom to study how the program works, and change it so it does your computing as you wish (freedom 1). Access to the source code is a precondition for this.
- The freedom to redistribute copies so you can help others (freedom 2).
- The freedom to distribute copies of your modified versions to others (freedom 3). By doing this you can give the whole community a chance to benefit from your changes. Access to the source code is a precondition for this.

One of the most popular free software license is the GNU General Public License (GNU GPL[3]).

The free software movement is supported by the Free Software Foundation (FSF[4]).

1.1.2 HURD

The HURD is an acronym for HIRD (HURD of interfaces representing depth) of Unix-replacing daemons. It is the GNU project's replacement for the Unix kernel. It is a collection of servers that run on the Mach microkernel to implement file systems, network protocols, file access control, and other features that are implemented by the Unix kernel or similar kernels (such as Linux).

The purpose of the GNU HURD is to improve your freedom on your operating system by allowing you to either add or remove a feature of the kernel on the fly.

From early on, the HURD was developed to use GNU Mach as the microkernel. This was a technical decision made by Richard Stallman, who thought it would speed up the work by saving a large part of it. He has admitted that he was wrong about that.

---

[1] See `https://en.wikipedia.org/wiki/Unix`

[2] `http://www.gnu.org/gnu/manifesto.html`

[3] `http://www.gnu.org/licenses/gpl.html`

[4] `https://www.fsf.org`

Nevertheless, development of the HURD is increasingly attracting developers and GNU/HURD systems exist and are usable.

1.1.3 Linux

Linux is a monolithic kernel created by Linus Torvalds in 1991. Linus Torvalds initially wrote a terminal emulator, which he used to access the large UNIX servers of his university. He wrote the program specifically for the hardware he was using and independent of an operating system because he wanted to use the functions of his new PC with an 80386 processor. This later became the kernel Linux.

Initially, Torvalds first published the kernel Linux under its own licence, which had a restriction on commercial activity.

In the notes for the first release of the kernel Linux, Torvalds lists the GNU software that is required to run Linux:

> Sadly, a kernel by itself gets you nowhere. To get a working system you need a shell, compilers, a library etc. [...] Most of the tools used with linux are GNU software and are under the GNU copyleft.

In 1992, he suggested releasing the kernel under the GNU General Public License. He first announced this decision in the release notes of version 0.12. In the middle of December 1992 he published version 0.99 using the GNU GPL.

The kernel Linux is now a contribution of many professionals and volonteers around the world.

1.1.4 Linux-libre

Linux, the kernel developed and distributed by Linus Torvalds et al, contains non-Free Software[5], i.e., software that does not respect your essential freedoms, and it induces you to install additional non-Free Software that it doesn't contain.

GNU Linux-libre[6] is a project to maintain and publish 100% Free distributions of Linux, suitable for use in Free System Distributions[7], removing software that is included without source code, with obfuscated or obscured source code, under non-Free Software licenses, that do not permit you to change the software so that it does what you wish, and that induces or requires you to install additional pieces of non-Free Software.

You can visit `https://h-node.org` to see if your hardware works with Linux-libre: wireless card and graphics chip in particular.

1.1.5 References

For more information on the GNU project and its relation with the kernel Linux, you can read `http://www.gnu.org/gnu/thegnuproject.html` and `http://www.gnu.org/gnu/gnu-linux-faq.html`.

For more information on the history of the HURD, I recommend you to read `http://web.archive.org/web/20221122061739/http://www.h-online.com/open/features/GNU-HURD-Altered-visions-and-lost-promise-1030942.htm`.

For more information on the HURD, read `http://www.gnu.org/software/hurd/`.

For more information on the early versions of the kernel Linux, read `https://www.cs.cmu.edu/~awb/linux.history.html`.

---

[5] For more information about the presence of proprietary firmware in the kernel Linux, read `http://www.fsfla.org/ikiwiki/anuncio/2010-03-Linux-2.6.33-libre.en` and `http://www.gnu.org/distros/free-system-distribution-guidelines.html#nonfree-firmware`.

[6] `http://www.fsfla.org/ikiwiki/selibre/linux-libre/index.en.html`

[7] For a full list of free as in freedom GNU/Linux distributions, see `http://www.gnu.org/distros/`.

1.2 Purpose of this Document

One day I found a Dell Optiplex 745 minitower with a Pentium 4 CPU in a municipal waste. I just replaced the button battery and the computer was able to boot. I decided to adapt GLLFSC document I previously wrote for the Lemote Yeeloong 8133 (with a Loongson 3A CPU): GNU/Linux[8] Libre from Source Code for Pentium 4 was born.

GLLFSC is a document that you follow to produce a command-line operating system. This OS is completely Free Software[9] and has enough programs on it so that you can:

- boot
- connect to the internet, either with wired or wireless connection
- browse the web with lynx
- read your mail with inetutils
- and thanks to Package Users and recipes, build new packages to extend its base features: graphical interface with Xorg, dynamic window manager dwm, gtk, palemoon web browser, and many more.

Why did I create GLLFSC?

1. It is 100% Free Software, no restriction on how or how long I can use any program in it
2. It is simple: simple to tweak things to fit my needs. This simplicity leads to both speed and reliability, 2 qualities I value very much in an OS.
3. It is extensible: if something is missing, adding it is simple with the use of Package Users recipes

[8] Note: in this document, we use the term "GNU/Linux" to name the entire system and "Linux" to name the kernel. For more information, read `http://www.gnu.org/gnu/why-gnu-linux.html`.

[9] `http://www.gnu.org/philosophy/free-sw.html`

2 Prerequisites

2.1 Definitions

2.1.1 `sysroot`

The traditional way of building a GNU/Linux operating system consists on building a (cross-) compilation toolchain to build a temporary operating system which in turn will be used to build the target system[1]. This requires almost as much time to complete the temporary system as to build the target one. Using sysroot resolves this problem.

From GCC installation manual, under Cross-Compiler-Specific Options:

`--with-sysroot`
`--with-sysroot=`*dir*

> Tells GCC to consider *dir* as the root of a tree that contains (a subset of) the root filesystem of the target operating system. Target system headers, libraries and run-time object files will be searched in there. More specifically, this acts as if `--sysroot=`*dir* was added to the default options of the built compiler. The specified directory is not copied into the install tree, unlike the options `--with-headers` and `--with-libs` that this option obsoletes. The default value, in case `--with-sysroot` is not given an argument, is `${gcc_tooldir}/sys-root`. If the specified directory is a subdirectory of `${exec_prefix}`, then it will be found relative to the GCC binaries if the installation tree is moved.
>
> This option affects the system root for the compiler used to build target libraries (which runs on the build system) and the compiler newly installed with `make install`; it does not affect the compiler which is used to build GCC itself.

2.1.2 Toolchain

According to Wikipedia[2]:

> In software, a toolchain is the set of programming tools that are used to create a product (typically another computer program or system of programs). The tools may be used in a chain, so that the output of each tool becomes the input for the next, but the term is used widely to refer to any set of linked development tools.
>
> A simple software development toolchain consists of a text editor for editing source code, a compiler and linker to transform the source code into an executable program, libraries to provide interfaces to the operating system, and a debugger.

2.1.3 `build`, `host` and `target`

During a cross-compilation, `build` `host` and `target` are among the most used options: understanding the precise meaning of those parameters is very important. We could define them thus:

- `--build=`*platform on which the program is compiled*,
- `--host=`*platform on which the program will run*,
- `--target=`*platform for which the program will create output*.

Let's use GCC as an example to explain the role of those three parameters.

During GCC compilation, we use: '`./configure --build=`*build-platform* `--host=`*host-platform* `--target=`*target-platform* `[various compilation parameters]`'

[1] see Chapter 10 [Further Readings], page 93, for more details

[2] `https://en.wikipedia.org/wiki/Toolchain`

So in those configuration parameters:

- `--build` provides the name of the platform currently running. If we were using an Intel Pentium processor to compile the system, our *build-platform* would be something like '`i686-pc-linux-gnu`'.

  If this parameter is not specified, it will be guessed automatically.

- `--host` represents the type of machine we are going to run GCC on after the compilation succeeds. During a cross-compilation this has to be specified, because the current machine can not know which architecture we wish to target. We want to produce executables to run on *Pentium4*, but there is currently no way we can specify '`Pentium4`' directly; because of this we specify '`i386-unknown-linux-gnu`'.

  `--host` can also be left unspecified and, in that case, *host-platform* would automatically define itself as *build-platform*, but this is not cross-compilation anymore.

  > **Note:** when `--build` and `--host` are different, configuration files will maintain the cross-compilation mode.

- `--target` defines the system for which compiler tools will create output.

  target-platform parameter is useful only for a limited number of programs. Although this parameter is often present when issuing '`./configure --help`', hardly any packages will need it.

  This parameter is only useful for performing tasks with different platforms; for instance, executable files compiled for different platforms can have a totally different code.

If we summarize, we have:

- *build-platform*: automatically guessed from platform in use; has to be specified if not guessed.
- *host-platform*: if unspecified, automatically equals *build-platform*. When *build-platform* and *host-platform* values are identical, it is a local compilation; otherwise it is a cross-compilation.
- *target-platform*: defines the system for which compiler tools will create output; it equals *host-platform* if unspecified. GCC, binutils, and programs related to the platform's instructions have this parameter; most programs do not use this parameter.

2.1.4 FHS

The Filesystem Hierarchy Standard (FHS) has been created to specify the location and use of main directories on a GNU/Linux operating system. Common commands, user data, libraries have to be put inside a specific directory given in the standard. In this document, FHS is not respected: for instance, binaries are all located in `/usr/bin`, while `bin`, `/sbin` and `/usr/sbin` are symbolic links to it.

2.2 Commands

Because most commands are common for a regular Unix user, only uncommon commands are explained in this document. If you do not understand a command that is not explained, you can use the documentation available on your computer; in a terminal, typing '`man` *`command`*' should give you enough information. For GNU software, '`info` *`package`*' can also give additional information.

To know more about command line, I suggest you read "Introduction to the Command Line" which is available on `https://archive.flossmanuals.org.uk/command-line/`.

3 Preliminary Work

Important: In order to complete the first steps of this chapter, you will need to have root permissions.

3.1 Package Users Introduction

Package Users is an interesting way of managing packages. Quotation from the project:

- You want to know which packages your files belong to?
- You want to deinstall software that doesn't have make uninstall?
- You are bothered by programs installed setuid root behind your back?
- You don't like packages quietly overwriting files from other packages?
- You don't like package managers like RPM?

YOU WANT TOTAL CONTROL USING ONLY UNIX BUILTINS?

The idea is to create one pair '`user`':'`group`' per package to be installed: a Package User. Every Package User is part of an '`install`' group in order to be able to write in directories that are usually owned by the root user. In order to avoid that one package replaces a file or a directory installed by another one, the directories owned by the '`install`' group have the sticky attribute for users and groups other than the Package Users and the install group. For more details, read `https://www.linuxfromscratch.org/hints/downloads/files/more_control_and_pkg_man.txt`.

3.1.1 Package Installation

To install a package with Package Users, you first have to type:

```
install_package foo
```

This will:

- create the package user '`foo`',
- make package user '`foo`' a member of the '`install`' group,
- create the directory `/usr/src/foo`,
- copy the files from `/etc/pkgusr/skel-package` into `/usr/src/foo`,
- log you in as '`foo`'.

After that, you have to get the source file of the program '`foo`' and install it as the user '`foo`'. Most of the time, the steps are simple:

```
su foo
wget http://path-to-source.org/foo-version.tar.gz
tar xf foo-version.tar.gz
cd foo-version
./configure --prefix=
make
make install
cd ..
rm -rf foo-version
rm foo-version.tar.gz
exit 0
```

3.1.2 Package Removal

To remove the files installed by a package:

```
find / -user foo | xargs rm
```

Then remove the package user:

```
userdel foo
```

3.1.3 Package Information

To get information about files installed by package user *foo*, do:

```
list_package foo
```

Be aware that this command may take some time to complete because the hard drive is scanned for files owned by Package User *foo*.

3.2 Build OS

In the edition you are reading, GLLFSC 1.9.0 for Pentium 4 has been used to demonstrate that GLLFSC can build itself.

Because installing Package Users will modify the build OS, it is strongly recommended to have 3 partitions on your hard drive:

- one partition for the current OS you are using, for instance `/dev/sda1`
- one partition for the build OS, unmodified GLLFSC 1.9.0: for instance `/dev/sda2`
- one partition for the OS we will build, GLLFSC 1.9.1: for instance `/dev/sda3`

You can create and modify partitions with a program like `gparted`.

Then, to mount the hard drive partition dedicated to the build OS, for instance `/dev/sda2`:

```
mkdir /mnt/sda2
mount /dev/sda2 /mnt/sda2
```

Then, download GLLFSC 1.9.0 from `http://cjarry.org/gnu-linux/gllfsc/pentium4/gllfsc-pentium4-1.9.0-completed.tar.bz2` and extract it:

```
cd /mnt/sda2
tar xf /path/to/gllfsc-pentium4-1.9.0-completed.tar.bz2 --numeric-owner
cd
```

Finally, edit `/mnt/sda2/etc/fstab`, `/mnt/sda2/etc/runit/1` (to set your keyboard layout in particular), and `/boot/grub/grub.cfg` to your situation, so that you will be able to boot on GLLFSC 1.9.0:

```
nano /mnt/sda2/etc/fstab /mnt/sda2/etc/runit/1 /boot/grub/grub.cfg
```

> **Note:** commands in nano are displayed as in '^X'. The '^' character means `CTRL` key, so '^X' means *`CTRL-X`*: press *`CTRL`* and *`X`* keys simultaneously on the keyboard.

A minimal `/boot/grub/grub.cfg` for classical hard disk could be:

```
insmod ext2
set default=0
set timeout=5

menuentry 'GLLFSC 1.9.0' {
    echo 'Loading linux-libre-3.10.108-gnu...'
    linux (hd0,2)/boot/vmlinuz-3.10.108-gnu root=/dev/sda2 quiet
}
```

A minimal `/boot/grub/grub.cfg` for hard disk supporting AHCI (Advanced Host Controller Interface) could be:

```
insmod part_msdos
```

```
insmod ext2
set default=0
set timeout=5

menuentry 'GLLFSC 1.9.0' {
    echo 'Loading linux-libre-3.10.108-gnu...'
    linux (ahci0,msdos2)/boot/vmlinuz-3.10.108-gnu root=/dev/sda2 quiet
}
```

You can now reboot on `/dev/sda2` and login as root.

3.3 Tmux Usage

Tmux is a terminal multiplexer: it allows multiple terminal sessions to be accessed simultaneously in a single window. You can use it to read GLLFSC build instructions in a frame while building GLLFSC in another frame, both in the same window. First run it with:

```
tmux
```

Then, you can split your screen horizontally by pressing simultaneously `CTRL` and `B`, and then `%`. You can also split it vertically by pressing simultaneously `CTRL` and `B`, and then `"`. Finally you can navigate from one frame to another by pressing simultaneously `CTRL` and `B`, and then `LEFT ARROW`, `RIGHT ARROW`, `UP ARROW` or `DOWN ARROW`.

3.4 Work Directory Creation

To create the directory `/gllfsc` in which the system will be built:

```
mkdir -v /gllfsc
```

3.5 Setting up Required Environment Variables

`~/.bash_profile` is a personal initialization file that is read when Bash is invoked as an interactive login shell (`~` is the location of the user's home directory). To write the content of the default `~/.bash_profile` of package users:

```
cat > /etc/pkgusr/bash_profile << 'EOF'
exec env -i HOME=${HOME} TERM=${TERM} PS1=${PS1} /bin/bash
EOF
```

The first line creates the file `/etc/pkgusr/bash_profile` and opens it for writing until '`EOF`' (End Of File) is written in it.

The second line tells Bash to execute `/bin/bash` with the option `-i` (or `--ignore-environment`) which will make Bash start with an empty environment. Variables `HOME`, `TERM` and `PS1` define respectively the home directory of the current user, the terminal used and the primary prompt string displayed.

`~/.bashrc` is a personal initialization file that is read when Bash is invoked as an interactive shell but not a login one. To write the content of the file `~/.bashrc` for each Package User:

```
cat > /etc/pkgusr/bashrc << EOF
set +h
umask 022
alias less='less -ic'
#alias make='make -j4'
# Make prompt reflect that we are a package user.
export PROMPT_COMMAND='PS1="\[\e[35m\]\A-package \u:\W\[\e[00m\]> "'
#export PS1='\[\e[35m\]\A-\W\[\e[00m\]$ '
export LC_ALL=POSIX
```

```
export CROSS_HOST="$(echo $MACHTYPE |\
    sed "s/$(echo $MACHTYPE | cut -d- -f2)/cross/")"
export CROSS_TARGET="x86_64-unknown-linux-gnu"
#export MABI=n32
#export MABI=64
export MARCH=core2
export PATH=/gllfsc/cross-tools/bin:/usr/lib/pkgusr:/bin:/usr/bin
# Go to the home directory whenever we su to a package user.
#cd

unset CFLAGS
unset CXXFLAGS
EOF
#source ~/.bash_profile
```

'`set +h`' tells Bash to not locate nor remember commands (hash) as they are looked up for execution.

'`umask 022`' sets Bash process' file creation mask to '`022`'. This results in permissions of '755' for those files.

'`PS1="\[\e[35m\]\A-package \u:\W\[\e[00m\]> "`' sets the primary prompt strings. The primary prompt strings are the strings you see before the commands you type in the terminal. The part '`\A-package \u:\W`' means that the time, in 24-hour HH:MM format will be displayed, then a '-', the package user, a ':' and finally the basename of `$PWD`, as in '`19:33-package groff:bin`'. The part '`\$`' adds a dollar sign at the end, '`\[\e[35m\]`' colors the strings in purple and '`\[\e[00m\]`' gets the original color back. For other colors, you can browse `https://en.wikipedia.org/wiki/ANSI_escape_code`.

`LC_ALL` is a macro used to define a single locale to overwrite other `LC_*` and `LANG` environment variables so that language, numeric values, time and other locale-dependant values have all the same value. It is set to the standard POSIX locale.

The value of variable `CROSS_HOST` equals the value of variable `MACHTYPE` of the current machine (for instance '`x86_64-pc-linux-gnu`') modulo the second word, which is replaced by '`cross`' (i.e. '`x86_64-cross-linux-gnu`').

The value of variable `CROSS_TARGET` equals the value of variable `MACHTYPE` of the machine for which the system is built (i.e. '`x86_64-unknown-linux-gnu`').

The variable `MABI` defines the ABI (Application Binary Interface) for which the system will be built. `-mabi` is an option of GCC. n32/64 are for 64-bit CPUs only. 64 has 64-bit pointers and long integers, whereas n32 has 32-bit pointers and long integers. This does not apply to Core 2 machines.

The variable `MARCH` defines the architecture for which the system will be built. `-march` is an option of GCC (GNU Compiler Collection).

The variable `PATH` contains a colon-separated list of directories in which the shell looks for commands. The shell will first look for commands in `/gllfsc/cross-tools/bin`, then, if the command was not found, in `/usr/lib/pkgusr`, then in `/bin` and finally in `/usr/bin`. `/usr/lib/pkgusr` contains wrapper scripts to replace commands '`mkdir`', '`chgrp`', '`chown`', '`chmod`' and '`install`', so that permissions on files and folders are handled properly when using Package Users.

`unset` command removes the variable associated, here `CFLAGS` and `CXXFLAGS`. Those variables are used by GCC as extra flags given to the C compiler and the C++ compiler respectively.

3.6 Build Partition Creation

Note: You can list existing partitions with '`fdisk -l`' or '`lsblk`'.

Warning: All data on the partition you chose in the next command will be deleted.

To dedicate the partition `/dev/sda3` to the system build, and to define the filesystem to be used for it as '`ext3`':

```
mke2fs -t ext3 /dev/sda3 -L gllfsc-1.9.1
```

Option `-t` is followed by the type of filesystem to be used. The filesystem '`ext3`' is used as it is one of the most common filesystem used with the kernel Linux.

3.7 Mounting Partition

To mount the hard drive partition used to build the system, for instance `/dev/sda3`:

```
mount /dev/sda3 /gllfsc
```

Note: You may wish to automatically mount `/dev/sda3` under `/gllfsc` each time you boot from `/dev/sda2`. In this case, you can add the following line to your `/etc/fstab`:

```
/dev/sda3   /   ext3   defaults   0   0
```

3.8 Creating Compilation and Download Directories

```
mkdir -v /gllfsc/{build,download}
```

3.9 Downloads

3.9.1 Downloading Packages

Connect to the wired internet first with:

```
ifconfig eth0 up
dhcpcd eth0
```

Test the connection with:

```
ping -c3 gnu.org
```

The packages listed below are those used in this document.

Download those files under `/gllfsc/download`. You can use '`wget -nv URL`' to do this.

Note: In order to download all the packages automatically, you can:

```
wget http://cjarry.org/gnu-linux/gllfsc/pentium4/automate-gllfsc.sh
# Edit it to suit your needs:
nano automate-gllfsc.sh
chmod u+x automate-gllfsc.sh
./automate-gllfsc.sh
```

Then you have to run the generated `0-get-packages.sh`:

```
chmod u+x 0-get-packages.sh
cd /gllfsc/download
~/0-get-packages.sh
cd
```

Check that all files have been downloaded with:

```
ls -1 | wc -l
```

The command above should give 73.

Note: If you have trouble with a savannah mirror, you can have a full list of them at `http://download.savannah.gnu.org/mirmon/savannah/`. If you have trouble with a GNU mirror, you can have a full list of them at `http://www.gnu.org/prep/ftp.html`.

- Autoconf: `http://ftpmirror.gnu.org/autoconf/autoconf-2.69.tar.gz`.
- Automake: `http://ftpmirror.gnu.org/automake/automake-1.14.tar.gz`.
- Bash: `http://ftpmirror.gnu.org/bash/bash-4.2.tar.gz`.
- Bc: `http://ftpmirror.gnu.org/bc/bc-1.07.1.tar.gz`.
- Binutils: `http://ftpmirror.gnu.org/binutils/binutils-2.24.tar.bz2`.
- Bison: `http://ftpmirror.gnu.org/bison/bison-2.7.tar.gz`.
- Bootscripts: `http://ftp.clfs.org/pub/clfs/conglomeration/bootscripts-cross-lfs/bootscripts-cross-lfs-2.0.0.tar.xz`.
- Bzip2: `ftp://sourceware.org/pub/bzip2/bzip2-1.0.6.tar.gz`.
- CA-Certificates: `https://anduin.linuxfromscratch.org/sources/other/certdata.txt`
- Coreutils: `http://ftpmirror.gnu.org/coreutils/coreutils-8.19.tar.xz`.
- DHCPCD: `https://github.com/NetworkConfiguration/dhcpcd/archive/refs/tags/v6.1.0.tar.gz`.
- Diffutils: `http://ftpmirror.gnu.org/diffutils/diffutils-3.3.tar.xz`.
- E2fsprogs: `http://downloads.sourceforge.net/e2fsprogs/e2fsprogs-1.42.8.tar.gz`
- Ed: `http://ftpmirror.gnu.org/ed/ed-1.1.tar.bz2`.
- File: `ftp://ftp.astron.com/pub/file/file-5.16.tar.gz`.
- Findutils: `http://ftpmirror.gnu.org/findutils/findutils-4.4.2.tar.gz`.
- Flex: `http://downloads.sourceforge.net/flex/flex-2.5.37.tar.bz2`.
- Gawk: `http://ftpmirror.gnu.org/gawk/gawk-4.1.0.tar.gz`.
- GCC: `http://ftpmirror.gnu.org/gcc/gcc-4.7.3/gcc-4.7.3.tar.bz2`.
- Gdbm: `http://ftpmirror.gnu.org/gdbm/gdbm-1.11.tar.gz`.
- Gettext: `http://ftpmirror.gnu.org/gettext/gettext-0.18.3.1.tar.gz`.
- Glibc: `http://ftpmirror.gnu.org/glibc/glibc-2.18.tar.bz2`.
- Gmp: `http://ftpmirror.gnu.org/gmp/gmp-5.1.3.tar.bz2`.
- Gperf: `http://ftp.gnu.org/gnu/gperf/gperf-3.0.4.tar.gz`.
- Grep: `http://ftpmirror.gnu.org/grep/grep-2.15.tar.xz`.
- Groff: `http://ftpmirror.gnu.org/groff/groff-1.22.2.tar.gz`.
- GRUB: `http://ftpmirror.gnu.org/grub/grub-2.00.tar.gz`.
- Gzip: `http://ftpmirror.gnu.org/gzip/gzip-1.6.tar.gz`.
- Iana-Etc: `http://sethwklein.net/iana-etc-2.30.tar.bz2`.
- Inetutils: `http://ftpmirror.gnu.org/inetutils/inetutils-2.2.tar.gz`.
- Iproute2: `https://www.kernel.org/pub/linux/utils/net/iproute2/iproute2-3.10.0.tar.bz2`.
- Kbd: `https://www.kernel.org/pub/linux/utils/kbd/kbd-2.0.1.tar.gz`.
- Kmod: `https://www.kernel.org/pub/linux/utils/kernel/kmod/kmod-15.tar.gz`.
- Less: `http://www.greenwoodsoftware.com/less/less-458.tar.gz`.
- Libevent: `https://github.com/libevent/libevent/releases/download/release-2.0.22-stable/libevent-2.0.22-stable.tar.gz`

- Libpipeline: http://download.savannah.gnu.org/releases/libpipeline/libpipeline-1.3.0.tar.gz.
- Libtasn1: http://ftpmirror.gnu.org/libtasn1/libtasn1-3.4.tar.gz.
- Libtool: http://ftpmirror.gnu.org/libtool/libtool-2.4.2.tar.gz.
- Linux-Libre[1]. https://www.kernel.org/pub/linux/kernel/v3.x/linux-3.10.108.tar.xz, http://linux-libre.fsfla.org/pub/linux-libre/releases/old/gen6/3.10.108-gnu/deblob-3.10 and http://linux-libre.fsfla.org/pub/linux-libre/releases/old/gen6/3.10.108-gnu/deblob-check.
- Lynx: http://invisible-mirror.net/archives/lynx/tarballs/lynx2.8.9rel.1.tar.bz2.
- M4: http://ftpmirror.gnu.org/m4/m4-1.4.17.tar.bz2.
- Make: http://ftpmirror.gnu.org/make/make-4.0.tar.bz2.
- Man-db: http://download.savannah.gnu.org/releases/man-db/man-db-2.6.7.1.tar.xz.
- Man-Pages: https://www.kernel.org/pub/linux/docs/man-pages/Archive/man-pages-3.54.tar.bz2.
- Mpc: http://ftpmirror.gnu.org/mpc/mpc-1.0.1.tar.gz.
- Mpfr: http://ftpmirror.gnu.org/mpfr/mpfr-3.1.2.tar.bz2.
- Nano: http://ftpmirror.gnu.org/nano/nano-2.3.2.tar.gz.
- Ncurses: http://ftpmirror.gnu.org/ncurses/ncurses-5.9.tar.gz.
- Openssl: https://github.com/openssl/openssl/releases/download/OpenSSL_1_1_1/openssl-1.1.1.tar.gz.
- Patch: http://ftpmirror.gnu.org/patch/patch-2.7.1.tar.bz2.
- Perl: http://www.cpan.org/src/5.0/perl-5.18.1.tar.gz.
- Procps-ng: https://sourceforge.net/projects/procps-ng/files/Production/procps-ng-3.3.0.tar.gz.
- Psmisc: https://sourceforge.net/projects/psmisc/files/psmisc/Archive/psmisc-22.20.tar.gz.
- Readline: http://ftpmirror.gnu.org/readline/readline-6.2.tar.gz.
- Runit: https://smarden.org/runit/runit-2.1.2.tar.gz
- Sed: http://ftpmirror.gnu.org/sed/sed-4.2.2.tar.bz2.
- Shadow: https://github.com/shadow-maint/shadow/releases/download/4.6/shadow-4.6.tar.xz.
- Sysvinit: http://download.savannah.gnu.org/releases/sysvinit/sysvinit-2.88dsf.tar.bz2.
- Tar: http://ftpmirror.gnu.org/tar/tar-1.27.1.tar.bz2.
- Texinfo: http://ftpmirror.gnu.org/texinfo/texinfo-4.13a.tar.gz.
- Tmux: https://github.com/tmux/tmux/releases/download/1.8/tmux-1.8.tar.gz
- Tzcode: http://www.iana.org/time-zones/repository/releases/tzcode2013h.tar.gz.
- Tzdata: http://www.iana.org/time-zones/repository/releases/tzdata2013h.tar.gz.
- Udev: https://www.kernel.org/pub/linux/utils/kernel/hotplug/udev-175.tar.gz.

[1] The kernel Linux is shipped with proprietary firmware. The version called Linux-Libre exists without them, recent versions are available for download at http://www.fsfla.org/ikiwiki/selibre/linux-libre/.

- Util-Linux: `https://www.kernel.org/pub/linux/utils/util-linux/v2.24/util-linux-2.24.tar.bz2`.
- Wireless_tools: `https://hewlettpackard.github.io/wireless-tools/wireless_tools.29.tar.gz`.
- Wpa_supplicant: `http://w1.fi/releases/wpa_supplicant-2.7.tar.gz`.
- Wget: `http://ftpmirror.gnu.org/wget/wget-1.19.5.tar.gz`.
- XZ-Utils: `https://tukaani.org/xz/xz-5.0.8.tar.bz2`.
- Zlib: `http://www.zlib.net/fossils/zlib-1.2.8.tar.gz`.

3.9.2 Downloading Patches

Download those files under `/gllfsc/download`.

- `http://www.fsfla.org/svn/fsfla/software/linux-libre/lemote/gnewsense/tags/3.10.108-gnu_0freeloong/100gnu+freedo.patch` this patch adds a picture of a GNU beside Freedo, Freedo being the mascot of Linux-Libre. The image can be seen on `http://www.fsfla.org/ikiwiki/selibre/linux-libre/100gnu+freedo`.

3.10 Final Preparations

3.10.1 Target Filesystem Hierarchy Creation

Note: You can automate the target filesystem creation with:

```
cd
csplit gllfsc-core2-1.9.1.texi '/subsection Target/' '{*}'

# Remove useless stuff:
nano xx02

# Make xx02 executable:
chmod u+x xx02

# Execute/run xx02:
./xx02
```

```
cd /gllfsc

# /usr is required for cmake, python and ruby at least
mkdir -v usr
cd usr
mkdir -v bin include lib share src
ln -sv bin sbin
ln -sv lib lib32
ln -sv lib lib64
cd ..

mkdir -v boot dev etc home local mnt opt proc root run static sys
mkdir -v cross-tools libexec

ln -sv usr/bin bin
ln -sv usr/bin sbin
ln -sv usr/include include
ln -sv usr/lib lib
```

```
ln -sv usr/lib lib32
ln -sv usr/lib lib64
ln -sv usr/share share
ln -sv usr/src src

install -dv -m 0777 tmp
install -dv -m 1777 var

cd var
mkdir -v cache local lock log mail run spool
mkdir -pv lib/misc lib/locate
cd ..

install -dv -m 0750 root

cd local
mkdir -v bin include lib src
ln -sv bin sbin
ln -sv lib lib32
mkdir -v share
cd share
mkdir -v doc info locale man misc terminfo zoneinfo
mkdir -v man/man{1..8}
cd ../..
ln -sv share/man man
mkdir service
cd
```

The command '`install -dv -m 1777 var`' creates the directory `var` with the permissions to read, write and execute for everyone. The '1' in '`1777`' is the sticky bit which allows deletion of the file or directory having this attribute only for the owner of the file or directory.

3.10.2 Target Filesystem Hierarchy Ownership

To make Package Users work on the target filesystem hierarchy, we need to change its ownership:

```
chown -Rv 0:10000 /gllfsc
chmod -Rv g+w,o+t /gllfsc 2>/dev/null
```

'`chown -Rv 0:10000 /gllfsc`' changes the ownership of the files and folders under `/gllfsc` to user '`0`' (root) and group '`10000`' (install).

'`chmod -Rv g+w,o+t /gllfsc`' changes the file mode bits of the files and folders under `/gllfsc` to give write rights to the group (with '`g+w`') and to add the sticky bit to others (with '`o+t`') so that the files and folders installed by a Package User cannot be replaced by another one.

3.10.3 Creating needed user, groups and log files

Note: You can automate the creation of needed user, groups and log files with:

```
csplit xx03 '/chapter Building/' '{*}'

# Remove useless stuff:
nano xx01

chmod u+x xx01
```

```
    ./xx01
echo root::0:0:root:/root:/bin/bash > /gllfsc/etc/passwd
```

The file `/etc/passwd` contains one line for each user account, with seven fields delimited by colons. These fields are:

- login name;
- optional encrypted password;
- numerical user ID;
- numerical group ID;
- user name or comment field;
- user home directory;
- optional user command interpreter.

The first line creates the file `/gllfsc/etc/passwd` and opens it for writing until '`EOF`' (End Of File) is written in it.

```
cat > /gllfsc/etc/group << EOF
root:x:0:
bin:x:1:
sys:x:2:
kmem:x:3:
tty:x:4:
tape:x:5:
daemon:x:6:
floppy:x:7:
disk:x:8:
lp:x:9:
dialout:x:10:
audio:x:11:
video:x:12:
utmp:x:13:
usb:x:14:
cdrom:x:15:
EOF
```

The file `/etc/group` is a text file which defines the groups on the system. There is one entry per line, with the following format: '`group_name:password:GID:user_list`'.

```
touch /gllfsc/var/run/utmp \
    /gllfsc/var/log/{btmp,lastlog,wtmp}
chmod -v 664 /gllfsc/var/run/utmp \
    /gllfsc/var/log/lastlog
```

```
cat > /root/.bash_profile << EOF
# Tab-complete package users when using su, finger or pinky
complete -o default -o nospace -A user su finger pinky
EOF
```

4 Building the Cross-Compilation Toolchain

In this chapter, the cross-compilation toolchain is built as well as core components of the target system. Those will then be used to build the target system. The build process of the cross-compilation toolchain takes about 2h30 on my Lenovo ThinkPad X200.

Note: You can automate parts of this chapter with:

```
wget http://cjarry.org/gnu-linux/gllfsc/core2/automate-gllfsc.sh
# Edit it to suit your needs:
nano automate-gllfsc.sh
chmod u+x automate-gllfsc.sh
./automate-gllfsc.sh
```

Then you have to split the generated `1-build-cross.sh` into instructions for each Package User:

```
csplit 1-build-cross.sh '/su -/' '{*}'
rm xx00 xx01 xx03
mv xx02 4.1-linux-headers
mv xx04 4.2-binutils
mv xx05 4.3-gcc-1
mv xx06 4.4-glibc
mv xx07 4.5-gcc-2
mv xx08 5.1-file
mv xx09 5.2-groff
mv xx10 5.3-shadow
mv xx11 5.4-m4
mv xx12 5.5-ncurses

chmod o+x 4.* 5.*
```

Then, with '`nano`', you can replace the first line beginning with '`su -`' by the two lines '`set -e`' and '`set -v`' at the beginning of each script so that it will exit on error and print each instruction before executing it:

```
nano 4.* 5.*
```

Change the rights on `/root` so that a Package User can read it:

```
chmod o+rx /root
```

Then, once inside the, for instance, linux-headers User personal directory:

```
/root/4.1-linux-headers
```

4.1 Target Linux-Headers

In this document, the kernel used is version 3.10.108 of Linux-libre.

Some changes made in the kernel since 3.14 require the non-free firmware of the radeon driver earlier at boot: without the firmware, the screen will remain blank on a machine that requires it, making the computer unusable.[1]

```
su - linux-headers
# 60 minutes mostly to deblob the kernel
cd /gllfsc/build

tar xf /gllfsc/download/linux-3.10.108.tar.xz
cd linux-3.10.108
```

[1] See `https://bugzilla.kernel.org/show_bug.cgi?id=77861` for details.

```
cp /gllfsc/download/deblob-3.10 .
cp /gllfsc/download/deblob-check .

chmod u+x deblob*

# 47 minutes for the following command
./deblob-3.10 --force

rm deblob*
cd ..

# About 1 minute for the following command (491 MB)
tar -cf linux-libre-3.10.108-gnu.tar linux-3.10.108

# 12 minutes for the following command (69 MB)
# (requires ~840 MB of RAM)
xz -9 linux-libre-3.10.108-gnu.tar

#mv linux-libre-3.10.108-gnu.tar /gllfsc/download
mv linux-libre-3.10.108-gnu.tar.xz /gllfsc/download

cd linux-3.10.108

make mrproper
make ARCH=x86_64 headers_check
make ARCH=x86_64 INSTALL_HDR_PATH=dest headers_install
cp -rv dest/include/* /gllfsc/include
cd ..
rm -rf linux-3.10.108
cd

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/include/scsi

exit 0
```

If the build is interrupted for some reason and you want to log back in as user "linux-headers":

```
su - linux-headers
```

With the command `su`, it is possible to change the user ID. The option `-` provides an environment similar to what the user would expect had the user logged in directly.

'`60 minutes`' is the time it takes to build the package on Lenovo ThinkPad X200 with an Intel Core 2 Duo processor.

The command '`make mrproper`' cleans the sources.

We need to specify '`ARCH=x86_64`' as we are cross-compiling.

'`exit 0`' exits the Package User environment.

4.2 Cross Binutils

GNU Binutils (GNU binary utilities) is a collection of programs for manipulating binaries.

```
su - binutils
```

```
# 5 minutes
tar xf /gllfsc/download/binutils-2.24.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/binutils-2.24
mkdir -pv ../binutils-build
cd ../binutils-build
CC="gcc" AR="ar" \
    ../binutils-2.24/configure \
    --prefix=/gllfsc/cross-tools \
    --build=${CROSS_HOST} \
    --host=${CROSS_HOST} \
    --target=${CROSS_TARGET} \
    --enable-64-bit-bfd \
    --with-sysroot=/gllfsc \
    --disable-nls \
    --enable-shared
make configure-host
make
make install
cp -v ../binutils-2.24/include/libiberty.h \
    /gllfsc/include
cd ..
rm -rf binutils-build
rm -rf binutils-2.24
cd

# Fix permissions for Package Users:
cd /gllfsc/cross-tools
chmod g+w,o+t bin
chmod g+w,o+t x86_64-unknown-linux-gnu{,/lib}
chmod g+w,o+t share
chmod g+w,o+t share/man{,/man1}
chmod g+w,o+t share/info{,/dir}
cd

exit 0
```

'`CC="gcc"`' and '`AR="ar"`' are flags that tell the `configure` script to use the local commands `gcc` as the C compiler and `ar` as the program that handles archives.

`--prefix=/gllfsc/cross-tools` tells the configure script to install architecture-independant files in `/gllfsc/cross-tools`.

The option `--enable-64-bit-bfd` enables 64 bit for BFD (the Binary File Descriptor).

`--with-sysroot=/gllfsc` tells Binutils to consider `/gllfsc` as the root of a tree that contains (a subset of) the root filesystem of the target operating system. Target system headers, libraries and run-time object files will be searched in there.

The `--enable-nls` option enables Native Language Support (NLS), which lets Binutils output diagnostics in languages other than American English. Native Language Support is enabled by default if not doing a canadian cross build. The `--disable-nls` option disables NLS.

The option `--enable-shared` is used to build shared versions of libraries, if shared libraries are supported on the target platform. Use `--disable-shared` to build only static libraries.

4.3 Cross GCC (C support only)

GCC is the GNU Compiler Collection. It can compile many languages, of which only C and C++ will be enabled in this document.

In this section, we build a minimal GCC in order to build glibc.

> **Warning:** to build GMP (a GCC dependency), you need a version of GCC different from 4.3.2 on your system[2]:
>
> GCC 4.3.2 miscompiles GMP on 64-bit machines; please use a different gcc version (e.g., gcc 4.3.1 and gcc 4.3.3 both work properly). We have not been able to find any workaround for this gcc bug. Unfortunately, Debian 5.0 has decided to stay with this trouble gcc version, resulting in that many users strike this bug.

```
su - gcc
# 20 minutes
tar xf /gllfsc/download/gcc-4.7.3.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/gcc-4.7.3
tar xf /gllfsc/download/gmp-5.1.3.tar.bz2
mv gmp-5.1.3 gmp
tar xf /gllfsc/download/mpc-1.0.1.tar.gz
mv mpc-1.0.1 mpc
tar xf /gllfsc/download/mpfr-3.1.2.tar.bz2
mv mpfr-3.1.2 mpfr
# Fix undefined reference to `__stack_check_guard' when compiling
# glibc:
sed -i '/k prot/agcc_cv_libc_provides_ssp=yes' gcc/configure
mkdir -pv ../gcc-build
cd ../gcc-build
../gcc-4.7.3/configure \
    --prefix=/gllfsc/cross-tools \
    --build=${CROSS_HOST} \
    --host=${CROSS_HOST} \
    --target=${CROSS_TARGET} \
    --with-sysroot=/gllfsc \
    --disable-multilib \
    --with-newlib \
    --disable-nls \
    --disable-shared \
    --disable-threads \
    --enable-languages=c \
    --with-mpfr-include="/gllfsc/build/gcc-4.7.3/mpfr/src" \
    --with-mpfr-lib="/gllfsc/build/gcc-build/mpfr/src/.libs" \
    --disable-decimal-float
# fixes bid_decimal_globals: fenv.h: No such file or directory

make all-gcc
make all-target-libgcc
make install-gcc
make install-target-libgcc
cd ..
rm -r gcc-build
rm -r gcc-4.7.3
```

[2] https://gmplib.org/#STATUS

```
cd

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/cross-tools/{include,lib}

exit 0
```

`--disable-multilib` specifies that multiple target libraries to support different target variants[3], calling conventions, etc. should not be built. The default is to build a predefined set of them.

`--with-newlib` specifies that '`newlib`' is being used as the target C library.

`--disable-threads` specifies that threading support should be disabled.

`--enable-languages=c` specifies that only the C compiler and its runtime libraries should be built.

GCC provides a low-level runtime library, `libgcc.a` or `libgcc_s.so.1` on some platforms. GCC generates calls to routines in this library automatically, whenever it needs to perform some operation that is too complicated to emit inline code for. This is built with '`make all-target-libgcc`' and installed with '`make install-target-libgcc`'

4.4 Target glibc

Glibc is the GNU C library. It provides macros, type definitions, and functions for tasks like string handling, mathematical computations, input/output processing, memory allocation and several other operating system services.

You need Gawk on your system to compile this library from source.

```
su - glibc
# 20 minutes
tar xf /gllfsc/download/glibc-2.18.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/glibc-2.18
# Make 4.0 can be used to build glibc 2.18:
sed -i.orig '4775s/3.79\* | 3.\[89\]\*/& | 4.0/' configure
#sed -i.orig "s/ -lgcc_eh\| -lgcc_s//g" Makeconfig
#echo "" > ports/sysdeps/mips/mips64/n64/Makefile
#echo "" > ports/sysdeps/mips/mips64/n32/Makefile
#echo "" > ports/sysdeps/mips/mips32/Makefile
#sed -i "/default) machine=/s/n32/${MABI}/g" \
#    ports/sysdeps/mips/preconfigure
mkdir -pv ../glibc-build
cd ../glibc-build

cat > config.cache << EOF
libc_cv_c_cleanup=yes
libc_cv_slibdir=/lib
EOF

cat > configparms << EOF
install_root=/gllfsc
libdir=/lib
EOF
```

[3] Such as different ABI, for instance n32 and 64.

```
BUILD_CC="gcc" \
    CC="${CROSS_TARGET}-gcc -march=${MARCH}" \
    AR="${CROSS_TARGET}-ar" \
    RANLIB="${CROSS_TARGET}-ranlib" \
    ../glibc-2.18/configure \
    --prefix= \
    --libexecdir=/lib/glibc \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --disable-nls \
    --disable-profile \
    --enable-add-ons \
    --with-tls \
    --enable-kernel=3.10 \
    --with-__thread \
    --with-binutils=/gllfsc/cross-tools/bin \
    --with-headers=/gllfsc/include \
    --enable-obsolete-rpc \
    --cache-file=config.cache

make

make install

cd ..
rm -rf glibc-build
rm -rf glibc-2.18
cd

cat > /gllfsc/etc/nsswitch.conf << EOF
passwd: files
group: files
shadow: files

hosts: files dns
networks: files

protocols: files
services: files
ethers: files
rpc: files
EOF

cat > /gllfsc/etc/ld.so.conf << EOF
/local/lib
EOF

# Make dir group-writable:
chmod g+w /gllfsc/share/info/dir
#mv /gllfsc/share/info/dir{,.glibc}

# Fix permissions for Package Users:
```

```
chmod g+w,o+t /gllfsc/include/sys
chmod g+w,o+t /gllfsc/share/info
chmod g+w,o+t /gllfsc/share/locale
chmod g+w,o+t /gllfsc/share/locale/*/LC_MESSAGES

exit 0
```

The file `config.cache` is used to attribute values to variables of the configure script.

'`libc_cv_forced_unwind=yes`' is used to avoid the error message '`error: forced unwind support is required`'.

'`libc_cv_c_cleanup=yes`' is used to avoid the error message '`error: the compiler must support C cleanup handling`'.

'`libc_cv_slibdir=/lib`' defines `/lib` as the directory in which the C library of the target system will be installed, instead of `/lib64` or `/lib32`.

You can install glibc in a different location than where you configured it to go by setting the `install_root` variable on the command line for '`make install`'. The value of this variable is prepended to all the paths for installation. This is useful when setting up a chroot environment or preparing a binary distribution. The directory should be specified with an absolute file name.

Files listed in '`install-lib`' are installed in the directory specified by '`libdir`' in `configparms` or `Makeconfig`.

'`CC="${CROSS_TARGET}-gcc -march=${MARCH}"`' sets `CC` to the cross-compiler for the target's architecture, processor and ABI we configured the library for. `AR` and `RANLIB` are set to cross-compiling versions of `ar` and `ranlib` as the native tools are not configured to work with object files for the target we configured for.

`--prefix=` tells the `configure` script to install glibc in the root directory (`/`) of the target system.

Unlike previous builds, `--host` now equals `${CROSS_TARGET}` instead of `${CROSS_HOST}`. This is because we are building the glibc version that the target system will use. We won't have to build it later.

Profiling can be of help to optimize a program by analysing memory use, the usage of particular instructions, etc. Option `--disable-profile` is used to disable this.

Option `--enable-add-ons` is used to enable all the add-on packages in the main source directory, which includes the glibc-ports used to support the MIPS architecture.

The option `--with-tls` tells the configure script to use TLS (thread-local storage). Thread-local storage is a computer programming method that uses memory local to a thread.

The '`3.10`' parameter given to option `--enable-kernel` describes the earliest version of the Linux kernel the generated library is expected to support. The higher the version number is, the less compatibility code is added, and the faster the code gets.

Option `--with-__thread` enables threads in glibc.

The option `--with-binutils=/gllfsc/cross-tools/bin` tells the `configure` script to use the binutils (assembler and linker) built in the cross-compilation toolchain process.

`--with-headers=/gllfsc/include` indicates the location of the kernel Linux' headers.

`--enable-obsolete-rpc` tells the `configure` script to install remote procedure call (RPC) headers. Those may be required by some programs.

`--cache-file=config.cache` specifies the file in which cache variables are listed for `configure`.

The file `/gllfsc/etc/nsswitch.conf` contains the configuration of NSS (Name Service Switch). NSS is a facility in Unix-like operating systems that provides a variety of sources for common configuration databases and name resolution mechanisms. These sources include

local operating system files (such as `/etc/passwd`, `/etc/group`, and `/etc/hosts`), the Domain Name System (DNS), the Network Information Service (NIS), and LDAP.

4.5 Cross GCC (C and C++ support)

In this section, we build a complete cross-compiler with support for C and C++ languages.

```
su - gcc
# 30 minutes
tar xf /gllfsc/download/gcc-4.7.3.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/gcc-4.7.3
tar xf /gllfsc/download/gmp-5.1.3.tar.bz2
mv gmp-5.1.3 gmp
tar xf /gllfsc/download/mpc-1.0.1.tar.gz
mv mpc-1.0.1 mpc
tar xf /gllfsc/download/mpfr-3.1.2.tar.bz2
mv mpfr-3.1.2 mpfr
mkdir -v ../gcc-build
cd ../gcc-build
../gcc-4.7.3/configure \
    --prefix=/gllfsc/cross-tools \
    --build=${CROSS_HOST} \
    --host=${CROSS_HOST} \
    --target=${CROSS_TARGET} \
    --with-sysroot=/gllfsc \
    --disable-nls \
    --enable-shared \
    --enable-__cxa_atexit \
    --disable-multilib \
    --enable-c99 \
    --enable-long-long \
    --enable-threads=posix \
    --enable-languages=c,c++ \
    --with-mpfr-include="/gllfsc/build/gcc-4.7.3/mpfr/src" \
    --with-mpfr-lib="/gllfsc/build/gcc-build/mpfr/src/.libs"
make
make install
cd ..
rm -rf gcc-build
rm -rf gcc-4.7.3
cd
exit 0
```

`--enable-__cxa_atexit` enables `__cxa_atexit`, rather than `atexit`, to register C++ destructors for local statics and global objects. This is essential for fully standards-compliant handling of destructors, but requires `__cxa_atexit` in libc.

`--enable-c99` enables support for the C99 standard.

`--enable-long-long` enables support for `long long int` types.

5 Building the Cross-Compilation Tools

The build process of the cross-compilation tools takes about 10 minutes on my Lenovo Thinkpad X200.

5.1 File

The command `file` is used to determine the type of a file: text, executable or data.

```
su - file
# 1 minute
tar xf /gllfsc/download/file-5.16.tar.gz -C /gllfsc/build
cd /gllfsc/build/file-5.16
./configure --prefix=/gllfsc/cross-tools
make
make install
cd ..
rm -rf file-5.16
cd

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/cross-tools/share/man/man{3,4,5}

exit 0
```

5.2 Groff

Groff is the GNU version of the roff document formatting system which is used to produce man pages.

You need G++ on your system to compile this program from source.

```
su - groff
# 3 minutes
tar xf /gllfsc/download/groff-1.22.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/groff-1.22.2
PAGE=A4 \
    ./configure \
    --prefix=/gllfsc/cross-tools \
    --without-x
make
make install
cd ..
rm -rf groff-1.22.2
cd
exit 0
```

'`PAGE=A4`' defines the default format of pages for printed output.

`--without-x` disables the dependency on the X window system.

5.3 Shadow

The package contains programs to handle users, groups and passwords in a secure way: passwords are encrypted.

```
su - shadow
```

```
# 1 minute
tar xf /gllfsc/download/shadow-4.6.tar.xz -C /gllfsc/build
cd /gllfsc/build/shadow-4.6

cat > shadow-4.6.patch << 'EOF'
diff -Nur shadow-4.6.orig/lib/commonio.c shadow-4.6/lib/commonio.c
--- shadow-4.6.orig/lib/commonio.c      2025-10-09 16:53:30.514854530 +0200
+++ shadow-4.6/lib/commonio.c   2025-10-09 13:18:06.084698074 +0200
@@ -266,16 +266,6 @@
                return NULL;
        }

-#ifdef HAVE_FCHOWN
-       if (fchown (fileno (fp), sb->st_uid, sb->st_gid) != 0) {
-               goto fail;
-       }
-#else                          /* !HAVE_FCHOWN */
-       if (chown (name, sb->st_mode) != 0) {
-               goto fail;
-       }
-#endif                         /* !HAVE_FCHOWN */
-
 #ifdef HAVE_FCHMOD
        if (fchmod (fileno (fp), sb->st_mode & 0664) != 0) {
                goto fail;
diff -Nur shadow-4.6.orig/lib/Makefile.am shadow-4.6/lib/Makefile.am
--- shadow-4.6.orig/lib/Makefile.am     2018-04-29 18:42:37.000000000 +0200
+++ shadow-4.6/lib/Makefile.am  2025-10-12 08:09:14.903424913 +0200
@@ -2,6 +2,7 @@
 AUTOMAKE_OPTIONS = 1.0 foreign

 DEFS =
+AM_CPPFLAGS = -DSYSCONFDIR=\"$(sysconfdir)\"

 noinst_LTLIBRARIES = libshadow.la

--- shadow-4.6.orig/lib/Makefile.in     2018-04-29 18:45:50.000000000 +0200
+++ shadow-4.6/lib/Makefile.in  2025-10-12 08:09:37.866137840 +0200
@@ -340,6 +340,7 @@
 top_build_prefix = @top_build_prefix@
 top_builddir = @top_builddir@
 top_srcdir = @top_srcdir@
+AM_CPPFLAGS = -DSYSCONFDIR=\"$(sysconfdir)\"
 AUTOMAKE_OPTIONS = 1.0 foreign
 noinst_LTLIBRARIES = libshadow.la
 libshadow_la_LDFLAGS = -version-info 0:0:0
diff -Nur shadow-4.6.orig/src/Makefile.am shadow-4.6/src/Makefile.am
--- shadow-4.6.orig/src/Makefile.am     2018-04-29 18:42:37.000000000 +0200
+++ shadow-4.6/src/Makefile.am  2025-10-11 22:30:08.389131714 +0200
@@ -3,11 +3,14 @@
        .indent.pro
```

```
 ubindir = ${prefix}/bin
-usbindir = ${prefix}/sbin
+usbindir = ${prefix}/bin
 suidperms = 4755
 sgidperms = 2755

 AM_CPPFLAGS = \
+        -DSYSCONFDIR=\"$(sysconfdir)\" \
+        -DSG=\"`echo sg | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`\" \
+        -DVIGR=\"`echo vigr | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`\" \
         -I${top_srcdir}/lib \
         -I$(top_srcdir)/libmisc \
         -DLOCALEDIR=\"$(datadir)/locale\"
@@ -124,13 +127,19 @@

 install-am: all-am
         $(MAKE) $(AM_MAKEFLAGS) install-exec-am install-data-am
-       ln -sf newgrp   $(DESTDIR)$(ubindir)/sg
-       ln -sf vipw     $(DESTDIR)$(usbindir)/vigr
+       ln -sf `echo newgrp | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'` \
+                $(DESTDIR)$(ubindir)/`echo sg | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`
+       ln -sf `echo vipw | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'` \
+                $(DESTDIR)$(usbindir)/`echo vigr | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`
         for i in $(suidbins); do \
-               chmod $(suidperms) $(DESTDIR)$(bindir)/$$i; \
+               chmod -f 4755 $(DESTDIR)$(bindir)/`echo $$i |\
+                sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`; \
         done
         for i in $(suidubins); do \
-               chmod $(suidperms) $(DESTDIR)$(ubindir)/$$i; \
+               chmod -f 4755 $(DESTDIR)$(ubindir)/`echo $$i |\
+                sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`; \
         done
 if WITH_TCB
         for i in $(shadowsgidubins); do \
diff -Nur shadow-4.6.orig/src/Makefile.in shadow-4.6/src/Makefile.in
--- shadow-4.6.orig/src/Makefile.in     2018-04-29 18:45:51.000000000 +0200
+++ shadow-4.6/src/Makefile.in  2025-10-11 22:26:21.423969169 +0200
@@ -509,10 +509,13 @@
         .indent.pro

 ubindir = ${prefix}/bin
-usbindir = ${prefix}/sbin
+usbindir = ${prefix}/bin
 suidperms = 4755
 sgidperms = 2755
 AM_CPPFLAGS = \
+       -DSYSCONFDIR=\"$(sysconfdir)\" \
+       -DSG=\"`echo sg | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`\" \
+       -DVIGR=\"`echo vigr | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`\" \
```

```
        -I${top_srcdir}/lib \
        -I$(top_srcdir)/libmisc \
        -DLOCALEDIR=\"$(datadir)/locale\"
@@ -1233,13 +1236,19 @@

 install-am: all-am
        $(MAKE) $(AM_MAKEFLAGS) install-exec-am install-data-am
-       ln -sf newgrp   $(DESTDIR)$(ubindir)/sg
-       ln -sf vipw     $(DESTDIR)$(usbindir)/vigr
+       ln -sf `echo newgrp | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'` \
+               $(DESTDIR)$(ubindir)/`echo sg | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`
+       ln -sf `echo vipw | sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'` \
+               $(DESTDIR)$(usbindir)/`echo vigr | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`
        for i in $(suidbins); do \
-               chmod $(suidperms) $(DESTDIR)$(bindir)/$$i; \
+               chmod -f 4755 $(DESTDIR)$(bindir)/`echo $$i | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`; \
        done
        for i in $(suidubins); do \
-               chmod $(suidperms) $(DESTDIR)$(ubindir)/$$i; \
+               chmod -f 4755 $(DESTDIR)$(ubindir)/`echo $$i | \
+               sed 's,^.*/,,;$(transform);s/$$/$(EXEEXT)/'`; \
        done
 @WITH_TCB_TRUE@        for i in $(shadowsgidubins); do \
 @WITH_TCB_TRUE@                chown root:shadow $(DESTDIR)$(ubindir)/$$i; \
EOF

patch -Np1 -i shadow-4.6.patch

sed -i.orig '/nscd_flush/s,^,//,' lib/commonio.c
cd src
sed -i.orig '/nscd_flush/s,^,//,' chfn.c chgpasswd.c chpasswd.c \
    chsh.c gpasswd.c groupadd.c groupdel.c groupmod.c grpck.c \
    grpconv.c grpunconv.c newusers.c passwd.c pwck.c pwconv.c \
    pwunconv.c useradd.c userdel.c usermod.c vipw.c
cd ..

sed -i.orig 's,"/etc,SYSCONFDIR",' lib/defines.h lib/getdef.c \
    lib/gshadow_.h lib/port.h libmisc/limits.c src/chsh.c \
    src/login_nopam.c src/logoutd.c src/suauth.c src/useradd.c

sed -i.orig '/amroot = .*uid/s,\((.*$\),1; /* \1 */,' src/chage.c \
    src/chsh.c src/passwd.c

sed -i.orig '/amroot.*bywho/s,\t(0 == bywho), 1 /* (0 == bywho) */,' \
    src/gpasswd.c
sed -i.orig 's,"sg",SG,' src/newgrp.c
sed -i.orig '/do_vipw = (/s,"vigr",VIGR,' src/vipw.c
sed -i.orig '/usbindir =/s,/sbin,/bin,' src/Makefile.{am,in}
```

```
sed -i.orig '/AM_CPPFLAGS =/s,=,= -DSYSCONFDIR=\\"$(sysconfdir)\\",' \
    libmisc/Makefile.{am,in}

#tar xf /gllfsc/download/gllfsc-core2-1.9.1-patches.tar.gz
#patch -Np1 -i shadow-4.6-sysroot_hacks-1.patch
#sed -i.orig \
#    's/bindir)\/\$\$i/bindir)\/mips64el-unknown-linux-gnu-\$\$i/' \
#    src/Makefile.am
#automake-1.11
#echo "shadow_cv_passwd_dir=/gllfsc/bin" > config.cache
#echo "ac_cv_func_lckpwdf=no" >> config.cache
./configure \
    --prefix=/gllfsc/cross-tools \
    --sbindir=/gllfsc/cross-tools/bin \
    --sysconfdir=/gllfsc/etc \
    --disable-shared \
    --without-audit \
    --without-libpam \
    --without-selinux \
    --program-prefix=${CROSS_TARGET}- \
    --cache-file=config.cache
sed -i.orig "/PASSWD_PROGRAM/s/passwd/${CROSS_TARGET}-&/" config.h
make
make install
cd ..
rm -rf shadow-4.6
cd
exit 0
```

`--without-audit`, `--without-libpam` and `--without-selinux` disable support for auditing, PAM (Pluggable authentication modules) and SELinux (Security-Enhanced Linux). We do not need those extra features.

`--program-prefix=${CROSS_TARGET}-` prepends the value of `CROSS_TARGET` (that is '`x86_64-unknown-linux-gnu`' in this document) to installed program names for cross-compilation.

5.4 M4

Bison 2.5 requires M4 to be built.

GNU M4 is a package containing an implementation of the m4 macro language. GNU M4 is used in GNU Autoconf' `configure` files.

```
su - m4
# 1 minute
tar xf /gllfsc/download/m4-1.4.17.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/m4-1.4.17
./configure --prefix=/gllfsc/cross-tools
make
make install
cd ..
rm -rf m4-1.4.17
cd
exit 0
```

5.5 Ncurses

GNU ncurses contains a library used to write text-based user interfaces in a terminal-independent manner.

```
su - ncurses
# 2 minutes
tar xf /gllfsc/download/ncurses-5.9.tar.gz -C /gllfsc/build
cd /gllfsc/build/ncurses-5.9
./configure \
    --prefix=/gllfsc/cross-tools \
    --without-shared \
    --disable-nls
make -C include
make -C progs tic
install -m755 progs/tic /gllfsc/cross-tools/bin
cd ..
rm -rf ncurses-5.9
cd
exit 0
```

`--without-shared` is used to avoid building the whole library as only `tic` is installed.

5.6 Cleaning up Cross-Compilation Toolchain

In order to save some space, binaries and libraries of cross-compilation tools can be stripped out.

> **Warning:** incorrect cleaning arguments used against library files can lead to library files breaking. For this reason, be careful of the command arguments. If you are not comfortable with this, you can skip this section as it will have no effect on the process of building the target system.

```
cd /gllfsc/cross-tools
strip --strip-all bin/*
strip --strip-debug lib/*
cd
```

`--strip-all` removes all symbols. This command reduces the size of the `bin` directory's content from 34 MB to 10 MB.

`--strip-debug` removes debugging symbols only. This command reduces the size of the `lib` directory's content from 16 MB to 15 MB.

6 Building the Target System

After having set up the cross-compilation toolchain and tools, the operating system for the target machine is built in this chapter. This build process takes about 2 hours on my Lenovo ThinkPad X200.

6.1 Setting up the Environment

Because this chapter is about the build of the target system and not the build of the cross-compilation toolchain and tools anymore, we need to update some environment variables.

For more convenience, we can set environment variables up in each Package User `~/.bashrc` file, so that this setup is preserved when logging in:

```
export CROSS_TARGET="x86_64-unknown-linux-gnu"
export MARCH="core2"

cat >> /etc/pkgusr/bashrc << EOF
export CC="${CROSS_TARGET}-gcc -march=${MARCH}"
export CXX="${CROSS_TARGET}-g++ -march=${MARCH}"
export AR="${CROSS_TARGET}-ar"
export AS="${CROSS_TARGET}-as"
export RANLIB="${CROSS_TARGET}-ranlib"
export LD="${CROSS_TARGET}-ld"
export STRIP="${CROSS_TARGET}-strip"
EOF
#source /etc/pkgusr/bash_profile
```

`CC` is the flag that indicates the C compiler to be used, `CXX` the C++ compiler, `AR` the archiver, `AS` the assembler, `RANLIB` the archives' index generator, `LD` the linker and `STRIP` the program for stripping.

All the programs to be used are prefixed with '`${CROSS_TARGET}-`' in order to use the cross-compilation toolchain instead of the toolchain of the host.

6.2 Automating the Build

You can automate parts of this chapter by splitting the script `2-build-target-system.sh` (see Chapter 4 [Building the Cross-Compilation Toolchain], page 17) into instructions for each Package User:

```
csplit 2-build-target-system.sh '/su -/' '{*}'
rm xx00
mv xx01 6.3-man-pages
mv xx02 6.4-zlib
mv xx03 6.5-binutils
mv xx04 6.6-gmp
mv xx05 6.7-mpfr
mv xx06 6.8-mpc
mv xx07 6.9-gcc
mv xx08 6.10-sed
mv xx09 6.11-e2fsprogs

mv xx10 6.12-coreutils
mv xx11 6.13-iana-etc
mv xx12 6.14-m4
```

```
mv xx13 6.15-bison
mv xx14 6.16-ncurses
mv xx15 6.17-libtool
mv xx16 6.18-readline
mv xx17 6.19-autoconf
mv xx18 6.20-automake
mv xx19 6.21-bash

mv xx20 6.22-bzip2
mv xx21 6.23-dhcpcd
mv xx22 6.24-diffutils
mv xx23 6.25-file
mv xx24 6.26-findutils
mv xx25 6.27-flex
mv xx26 6.28-gawk
mv xx27 6.29-gdbm
mv xx28 6.30-gettext
mv xx29 6.31-grep

mv xx30 6.32-groff
mv xx31 6.33-gzip
mv xx32 6.34-inetutils
mv xx33 6.35-iproute2
mv xx34 6.36-kbd
mv xx35 6.37-kmod
mv xx36 6.38-less
mv xx37 6.39-libpipeline
mv xx38 6.40-make
mv xx39 6.41-man-db

mv xx40 6.42-nano
mv xx41 6.43-patch
mv xx42 6.44-psmisc
mv xx43 6.45-shadow
mv xx44 6.46-sysvinit
mv xx45 6.47-tar
mv xx46 6.48-texinfo
mv xx47 6.49-udev
mv xx48 6.50-util-linux
mv xx49 6.51-xz-utils

mv xx50 6.52-bootscripts
mv xx51 6.53-linux-libre

# Edit 6.53-linux-libre and remove lines from "Processor" to
# "Bootup logo"
nano 6.53-linux-libre

mv xx52 6.54-grub
chmod o+x 6.*
```

Then, with '`nano`', you can remove lines beginning with '`su -`', and add the line '`set -e`' and the line '`set -v`' at the beginning of each script so that it will exit on error and print each instruction before executing it. To automate this step:

```
sed -i 's,su -.*,set -e\nset -v\n,' 6.*
```

Then, once inside the, for instance, man-pages User personal directory:

```
/root/6.2-man-pages
```

6.3 Man Pages

The man-pages package documents the kernel Linux and C library's interfaces that are used by user-space programs.

```
su - man-pages
# 1 minute
tar xf /gllfsc/download/man-pages-3.54.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/man-pages-3.54
make prefix=/gllfsc install
cd ..
rm -rf man-pages-3.54
cd
# shadow installs its own version of getspnam.3 and passwd.5:
mv -v /gllfsc/share/man/man3/getspnam.3{,.man-pages}
mv -v /gllfsc/share/man/man5/passwd.5{,.man-pages}

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/share/man
chmod g+w,o+t /gllfsc/share/man/man*

exit 0
```

The option `prefix=/gllfsc` is used to install the man pages on the target directory instead of the `/usr` directory of the host.

6.4 Zlib

Zlib is a compression/decompression library.

```
su - zlib
# 1 minute
tar xf /gllfsc/download/zlib-1.2.8.tar.gz -C /gllfsc/build
cd /gllfsc/build/zlib-1.2.8
./configure --prefix=
make AR="${AR}"
make prefix=/gllfsc install
cd ..
rm -rf zlib-1.2.8
cd

# Fix permissions for Package User e2fsprogs:
chmod g+w,o+t /gllfsc/lib/pkgconfig

exit 0
```

In order to build zlib by cross-compilation, the flag `AR` has to be equal to '`${AR}`'.

6.5 Binutils

GNU Binutils (GNU binary utilities) is a collection of programs for manipulating binaries.

```
su - binutils
# 5 minutes
tar xf /gllfsc/download/binutils-2.24.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/binutils-2.24
mkdir -pv ../binutils-build
cd ../binutils-build
../binutils-2.24/configure \
    --prefix= \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --target=${CROSS_TARGET} \
    --enable-64-bit-bfd \
    --enable-shared \
    --disable-nls
make configure-host
make tooldir=
make DESTDIR=/gllfsc tooldir= install
cp -v ../binutils-2.24/include/libiberty.h /gllfsc/include
cd ..
rm -rf binutils-build
rm -rf binutils-2.24
cd
# For autoconf:
mv /gllfsc/share/info/standards.info{,.binutils} -v
# For groff:
#mv /gllfsc/share/info/dir{,.binutils} -v
exit 0
```

The option `--host` is now set to `CROSS_TARGET` because the host that will run this build will be the target system.

6.6 GMP

GMP (GNU multiple precision arithmetic library) is required to build GCC.

```
su - gmp
# 2 minutes
tar xf /gllfsc/download/gmp-5.1.3.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/gmp-5.1.3
./configure \
    --host=${CROSS_TARGET} \
    --prefix= \
    --enable-cxx
make
make DESTDIR=/gllfsc install
rm -v /gllfsc/lib/lib{gmp,gmpxx}.la
cd ..
rm -rf gmp-5.1.3
cd
exit 0
```

The option `--enable-cxx` enables support for the C++ language.

The files `/gllfsc/lib/lib{gmp,gmpxx}.la` are removed to avoid the following error when building MPFR: '`/lib/libgmp.so: could not read symbols: File in wrong format`'.

6.7 MPFR

GNU MPFR (Multiple Precision Floating-Point Reliably) is a portable C library for arbitrary-precision binary floating-point computation with correct rounding.

```
su - mpfr
# 1 minute
tar xf /gllfsc/download/mpfr-3.1.2.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/mpfr-3.1.2
./configure \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
rm -v /gllfsc/lib/libmpfr.la
cd ..
rm -rf mpfr-3.1.2
cd

# Fix permissions for Package User procps-ng:
chmod g+w,o+t /gllfsc/share/doc

exit 0
```

The file `/gllfsc/lib/libmpfr.la` is removed to avoid the following error when building MPC: '`/lib/libmpfr.so: could not read symbols: File in wrong format`'.

6.8 MPC

GNU MPC (Multiple Precision Complex Library) is a C library for the arithmetic of complex numbers with arbitrarily high precision and correct rounding of the result.

```
su - mpc
# 1 minute
tar xf /gllfsc/download/mpc-1.0.1.tar.gz -C /gllfsc/build
cd /gllfsc/build/mpc-1.0.1
./configure \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf mpc-1.0.1
cd
exit 0
```

6.9 GCC

GCC is the GNU Compiler Collection.

```
su - gcc
# 25 minutes
tar xf /gllfsc/download/gcc-4.7.3.tar.bz2 -C /gllfsc/build
```

```
cd /gllfsc/build/gcc-4.7.3
sed -i.orig 's/install_to_$(INSTALL_DEST) //' libiberty/Makefile.in
sed -i.orig 's@\./fixinc\.sh@-c true@' gcc/Makefile.in
mkdir -v ../gcc-build
cd ../gcc-build
../gcc-4.7.3/configure \
    --prefix= \
    --libexecdir=/lib \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --target=${CROSS_TARGET} \
    --enable-shared \
    --enable-threads=posix \
    --enable-__cxa_atexit \
    --enable-c99 \
    --enable-long-long \
    --disable-multilib \
    --enable-clocale=gnu \
    --enable-languages=c,c++ \
    --disable-libstdcxx-pch \
    --disable-nls
make
make DESTDIR=/gllfsc install
ln -sv gcc /gllfsc/bin/cc
cd ..
rm -rf gcc-build
rm -rf gcc-4.7.3
cd

# Fix permissions for Package Users:
chmod g+w,o+t /lib/gcc /include/c++

exit 0
```

'`sed -i.orig 's/install_to_$(INSTALL_DEST) //' libiberty/Makefile.in`' is used as we already installed the library `libiberty.a` with Binutils.

Using `--enable-clocale=gnu` option ensures that the correct locale will automatically be chosen.

Option `--disable-libstdcxx-pch` disables support for precompiled headers (PCH).

The line '`ln -sv gcc /gllfsc/bin/cc`' creates a symbolic link `cc` that points to `gcc`.

6.10 Sed

GNU sed is a stream editor: it is used to perform basic text transformations on an input stream (a file or input from a pipeline).

```
su - sed
# 1 minute
tar xf /gllfsc/download/sed-4.2.2.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/sed-4.2.2
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
```

```
    --prefix= \
    --bindir=/bin \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf sed-4.2.2
cd
exit 0
```

6.11 E2fsprogs

E2fsprogs is a package that contains tools to handle the ext2, ext3 and ext4 filesystems.

```
su - e2fsprogs
# 2 minutes
tar xf /gllfsc/download/e2fsprogs-1.42.8.tar.gz -C /gllfsc/build
cd /gllfsc/build/e2fsprogs-1.42.8
mkdir -v build
cd build
../configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --with-root-prefix="" \
    --enable-elf-shlibs \
    --disable-nls
make
make DESTDIR=/gllfsc install
make DESTDIR=/gllfsc install-libs
cd ../..
rm -rf e2fsprogs-1.42.8
cd
rm -v /gllfsc/lib/lib{blkid,com_err,e2p,ext2fs,ss,uuid}.so
# util-linux installs its own versions:
mv -v /gllfsc/bin/blkid{,.e2fsprogs}
mv -v /gllfsc/bin/findfs{,.e2fsprogs}
mv -v /gllfsc/bin/fsck{,.e2fsprogs}
mv -v /gllfsc/bin/uuidgen{,.e2fsprogs}
mv -v /gllfsc/lib/libuuid.a{,.e2fsprogs}
mv -v /gllfsc/lib/libblkid.a{,.e2fsprogs}
mv -v /gllfsc/bin/uuidd{,.e2fsprogs}
mv -v /gllfsc/lib/libuuid.so.1{,.e2fsprogs}
mv -v /gllfsc/lib/libblkid.so.1{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man1/uuidgen.1{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_clear.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_compare.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_copy.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_generate.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_is_null.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_parse.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_time.3{,.e2fsprogs}
```

```
mv -v /gllfsc/usr/share/man/man3/uuid_unparse.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_generate_random.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/uuid_generate_time.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man3/libblkid.3{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man8/uuidd.8{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man8/blkid.8{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man8/findfs.8{,.e2fsprogs}
mv -v /gllfsc/usr/share/man/man8/fsck.8{,.e2fsprogs}

mv -v /gllfsc/usr/include/blkid/blkid.h{,.e2fsprogs}
mv -v /gllfsc/usr/lib/pkgconfig/uuid.pc{,.e2fsprogs}
mv -v /gllfsc/usr/lib/pkgconfig/blkid.pc{,.e2fsprogs}

mv -v /gllfsc/usr/include/uuid/uuid.h{,.e2fsprogs}

# Fix permissions for Package User util-linux:
chmod g+w,o+t /gllfsc/usr/include/blkid
chmod g+w,o+t /gllfsc/usr/include/uuid

exit 0
```

`--with-root-prefix=""` is used to put e2fsprogs binaries inside `/sbin` instead of *`PREFIX`*`/sbin` which would be `/sbin`.

Option `--enable-elf-shlibs` enables e2fsprogs shared libraries.

'`make DESTDIR=/gllfsc install-libs`' is used to install libraries, those are not installed with '`make DESTDIR=/gllfsc install`'.

The sequence of commands that follows first removes symbolic links `/gllfsc/lib/lib{blkid,com_err,e2p,ext2fs,ss,uuid}.so` which point respectively to abolute paths `/lib/lib{blkid,com_err,e2p,ext2fs,ss,uuid}.so`. In order to use the libraries of the target operating system, we need to symlink `/gllfsc/lib/lib{blkid,com_err,e2p,ext2fs,ss,uuid}.so` to their relative paths files.

6.12 Coreutils

GNU coreutils (core utilities) includes the standard programs for text and file manipulation.

```
su - coreutils
# 3 minutes
tar xf /gllfsc/download/coreutils-8.19.tar.xz -C /gllfsc/build
cd /gllfsc/build/coreutils-8.19
cat > config.cache << EOF
fu_cv_sys_stat_statfs2_bsize=yes
gl_cv_func_mbrtowc_incomplete_state=yes
gl_cv_func_mbrtowc_nul_retval=yes
gl_cv_func_mbrtowc_null_arg=yes
gl_cv_func_mbrtowc_retval=yes
gl_cv_func_btowc_eof=yes
gl_cv_func_wcrtomb_retval=yes
gl_cv_func_wctob_works=yes
gl_cv_func_fstatat_zero_flag=yes
EOF
./configure \
    --build=${CROSS_HOST} \
```

```
    --host=${CROSS_TARGET} \
    --prefix= \
    --enable-no-install-program=groups,hostname,kill,uptime \
    --cache-file=config.cache \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf coreutils-8.19
cd
exit 0
```

The variables listed in the file `config.cache` are used in order to avoid that the `configure` script evaluate their values: otherwise the build may fail when cross-compiling.

We use `--enable-no-install-program=groups,kill,uptime` in order not to install commands `groups`, `kill` and `uptime`. Those commands will be installed by the packages shadow and procps.

6.13 iana-etc

The iana-etc package installs services and protocols using data from the Internet Assigned Numbers Authority (IANA).

```
su - iana-etc
# 1 minute
tar xf /gllfsc/download/iana-etc-2.30.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/iana-etc-2.30
make
make DESTDIR=/gllfsc install
cd ..
rm -rf iana-etc-2.30
cd
exit 0
```

6.14 M4

GNU M4 is a package containing an implementation of the m4 macro language. GNU M4 is used in GNU Autoconf' `configure` files.

```
su - m4
# 1 minute
tar xf /gllfsc/download/m4-1.4.17.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/m4-1.4.17
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf m4-1.4.17
cd
exit 0
```

6.15 Bison

GNU bison parser generator.

```
su - bison
# 1 minute
tar xf /gllfsc/download/bison-2.7.tar.gz -C /gllfsc/build
cd /gllfsc/build/bison-2.7
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
#echo '#define YYENABLE_NLS 1' >> config.h
make
make DESTDIR=/gllfsc install
cd ..
rm -rf bison-2.7
cd

# Fix permissions for Package User libtool:
chmod g+w,o+t /gllfsc/share/aclocal

exit 0
```

6.16 Ncurses

```
su - ncurses
# 2 minutes
tar xf /gllfsc/download/ncurses-5.9.tar.gz -C /gllfsc/build
cd /gllfsc/build/ncurses-5.9
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --with-shared \
    --enable-widec \
    --without-debug \
    --without-ada \
    --with-build-cc="gcc -D_GNU_SOURCE" \
    --libdir=/lib \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf ncurses-5.9
cd

ln -sv ncursesw/curses.h /gllfsc/include/curses.h
ln -sv ncursesw/ncurses.h /gllfsc/include/ncurses.h
ln -sv ncursesw/term.h /gllfsc/include/term.h
ln -sfv libncursesw.so /gllfsc/lib/libncurses.so
```

```
exit 0
```

Option `--enable-widec` enables wide characters support in ncurses.

Option `--without-ada` disables support for the Ada programming language inside ncurses.

The command '`ln -sfv libncursesw.so /gllfsc/lib/libncurses.so`' creates the symlink `libcurses.so` so that programs that do not know `libncursesw.so` can be linked against it.

6.17 Libtool

GNU libtool is a generic library support script. It hides the complexity of using shared libraries behind a consistent, portable interface.

```
su - libtool
# 1 minute
tar xf /gllfsc/download/libtool-2.4.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/libtool-2.4.2
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf libtool-2.4.2
cd
exit 0
```

6.18 Readline

The GNU Readline library provides a set of functions for use by applications that allow users to edit command lines as they are typed in.

```
su - readline
# 1 minute
tar xf /gllfsc/download/readline-6.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/readline-6.2
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --libdir=/lib
make
make DESTDIR=/gllfsc install
make DESTDIR=/gllfsc install-doc
cd ..
rm -rf readline-6.2
cd
exit 0
```

6.19 Autoconf

GNU autoconf is an extensible package of M4 macros that produce shell scripts to automatically configure software source code packages. These scripts can adapt the packages to many kinds of UNIX-like systems without manual user intervention.

```
su - autoconf
```

```
# 1 minute
tar xf /gllfsc/download/autoconf-2.69.tar.gz -C /gllfsc/build
cd /gllfsc/build/autoconf-2.69
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf autoconf-2.69
cd
# Fix autom4te: need GNU m4 1.4 or later: /gllfsc/cross-tools/bin/m4
sed -i 's,/gllfsc/cross-tools,,' /gllfsc/bin/autom4te
exit 0
```

6.20 Automake

GNU automake is a tool for automatically generating `Makefile.in` files compliant with the GNU Coding Standards[1].

You need Autoconf on your system to compile this program from source.

```
su - automake
# 1 minute
tar xf /gllfsc/download/automake-1.14.tar.gz -C /gllfsc/build
cd /gllfsc/build/automake-1.14
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf automake-1.14
cd
exit 0
```

6.21 Bash

GNU Bash (Bourne again shell) is an sh-compatible shell that incorporates useful features from the Korn shell (ksh) and C shell (csh).

```
su - bash
# 2 minutes
tar xf /gllfsc/download/bash-4.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/bash-4.2
cat > config.cache << EOF
ac_cv_func_mmap_fixed_mapped=yes
ac_cv_func_strcoll_works=yes
ac_cv_func_working_mktime=yes
bash_cv_func_sigsetjmp=present
bash_cv_getcwd_malloc=yes
```

[1] `http://www.gnu.org/prep/standards/`

```
bash_cv_job_control_missing=present
bash_cv_printf_a_format=yes
bash_cv_sys_named_pipes=present
bash_cv_ulimit_maxfds=yes
bash_cv_under_sys_siglist=yes
bash_cv_unusable_rtsigs=no
gt_cv_int_divbyzero_sigfpe=yes
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --bindir=/bin \
    --cache-file=config.cache \
    --without-bash-malloc \
    --with-installed-readline \
    --disable-nls
make
make \
    DESTDIR=/gllfsc \
    htmldir=/share/doc/bash-4.2 \
    install
ln -sv bash /gllfsc/bin/sh
cd ..
rm -rf bash-4.2
cd

exit 0
```

The variables listed in the file `config.cache` are used in order to avoid that the `configure` script evaluate their values: otherwise the build may fail when cross-compiling.

Option `--without-bash-malloc` tells the `configure` script not to use the `malloc` function shipped with Bash. Glibc's version will be used instead.

Option `--with-installed-readline` tells the configure script to use the installed readline library instead of the one shipped with Bash.

'`ln -sv bash /gllfsc/bin/sh`' creates a symlink `sh` to `bash`.

6.22 Bzip2

Bzip2 is a package that contains utilities to compress and decompress files with a better original size/compressed size ratio than gzip.

```
su - bzip2
# 1 minute
tar xf /gllfsc/download/bzip2-1.0.6.tar.gz -C /gllfsc/build
cd /gllfsc/build/bzip2-1.0.6
sed -i.orig "/^all:/s/ test//" Makefile
sed -i.orig 's:ln -s -f $(PREFIX)/bin/:ln -s :' Makefile
make \
    -f Makefile-libbz2_so \
    CC="${CC}" \
    AR="${AR}" \
    RANLIB="${RANLIB}"
```

```
make clean
make \
    CC="${CC}" \
    AR="${AR}" \
    RANLIB="${RANLIB}"
make \
    PREFIX=/gllfsc \
    install
cp -av libbz2.so* /gllfsc/lib
ln -sv ../../lib/libbz2.so.1.0 /gllfsc/lib/libbz2.so
rm -v /gllfsc/bin/{bunzip2,bzcat,bzip2}
cp -v bzip2-shared /gllfsc/bin/bzip2
ln -sv bzip2 /gllfsc/bin/bunzip2
ln -sv bzip2 /gllfsc/bin/bzcat
cd ..
rm -rf bzip2-1.0.6
cd
exit 0
```

'`sed -i.orig "/^all:/s/ test//" Makefile`' is used to skip tests when building.

'`sed -i.orig 's:ln -s -f $(PREFIX)/bin/:ln -s :' Makefile`' is used in order to have relative path symlinks instead of absolute ones.

Option `-f Makefile-libbz2_so` is used to build shared libraries.

Flags `CC`, `AR` and `RANLIB` are used so that bzip2 is built using cross-compilation tools instead of the host's ones.

'`make clean`' is used to clean up temporary files.

The second build commands are used to build static libraries.

6.23 DHCPCD

DHCPCD is a wrapper for the DHCP (Dynamic Host Configuration Protocol) client daemon.

```
su - dhcpcd
# 1 minute
tar xf /gllfsc/download/v6.1.0.tar.gz -C /gllfsc/build
cd /gllfsc/build/dhcpcd-6.1.0
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --bindir=/sbin \
    --sysconfdir=/etc \
    --dbdir=/var/lib/dhcpcd \
    --libexecdir=/lib/dhcpcd \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf dhcpcd-6.1.0
cd
exit 0
```

6.24 Diffutils

GNU Diffutils is a package of several programs related to finding differences between files.

```
su - diffutils
# 1 minute
tar xf /gllfsc/download/diffutils-3.3.tar.xz -C /gllfsc/build
cd /gllfsc/build/diffutils-3.3
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf diffutils-3.3
cd
exit 0
```

6.25 File

```
su - file
# 1 minute
tar xf /gllfsc/download/file-5.16.tar.gz -C /gllfsc/build
cd /gllfsc/build/file-5.16
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf file-5.16
cd
exit 0
```

6.26 Findutils

The GNU Find Utilities are typically used to provide directory search and file locating capabilities.

```
su - findutils
# 1 minute
tar xf /gllfsc/download/findutils-4.4.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/findutils-4.4.2
cat > config.cache << EOF
gl_cv_func_wcwidth_works=yes
gl_cv_header_working_fcntl_h=yes
ac_cv_func_fnmatch_gnu=yes
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
```

```
    --libexecdir=/lib/locate \
    --localstatedir=/var/lib/locate \
    --cache-file=config.cache \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf findutils-4.4.2
cd
exit 0
```

6.27 Flex

Flex is a tool for generating scanners. A scanner, sometimes called a tokenizer, is a program which recognizes lexical patterns in text.

```
su - flex
# 1 minute
tar xf /gllfsc/download/flex-2.5.37.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/flex-2.5.37
# From http://sourceforge.net/p/flex/bugs/151/
sed -i.orig '1s/$/\n#undef malloc\n#undef realloc/' \
    lib/realloc.c
cat > config.cache << EOF
ac_cv_path_M4="/bin/m4"
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --cache-file=config.cache \
    --disable-nls
make
make DESTDIR=/gllfsc install
ln -sv libfl.a /gllfsc/lib/libl.a
cd ..
rm -r flex-2.5.37
cd

cat > /gllfsc/bin/lex << EOF
#!/bin/sh
exec /bin/flex -l \$@
EOF
chmod -v 755 /gllfsc/bin/lex
exit 0
```

`config.cache` forces flex to use `/bin/m4` instead of `/gllfsc/cross-tools/bin/m4` on the target machine.

For compatibility issues, we create the symlink `libl.a`.

We then create target system's `/bin/lex` that will execute `flex` with option `-l` in order to behave with maximal compatibility like `lex`.

6.28 Gawk

GNU awk (Gawk) is a program used to select particular records in a file and perform operations upon them.

```
su - gawk
# 2 minutes
tar xf /gllfsc/download/gawk-4.1.0.tar.gz -C /gllfsc/build
cd /gllfsc/build/gawk-4.1.0
sed -i.orig \
    '/check-recursive all-recursive/s/ check-for-shared-lib-support//' \
    extension/Makefile.in
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --libexecdir=/lib \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -r gawk-4.1.0
cd
exit 0
```

The sed expression is used to avoid the error '`Building the extensions is not supported on this platform`'.

6.29 Gdbm

GNU dbm is a library of database functions.

```
su - gdbm
# 1 minute
tar xf /gllfsc/download/gdbm-1.11.tar.gz -C /gllfsc/build
cd /gllfsc/build/gdbm-1.11
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -r gdbm-1.11
cd
# fix man-db's /lib/libpipeline.so: error adding symbols: File in
# wrong format
rm /gllfsc/lib/libgdbm.la
exit 0
```

6.30 Gettext

GNU gettext utilities are a set of tools that provides a framework to help packages produce multi-lingual messages.

```
su - gettext
# 7 minutes
tar xf /gllfsc/download/gettext-0.18.3.1.tar.gz -C /gllfsc/build
cd /gllfsc/build/gettext-0.18.3.1
cat > config.cache << EOF
am_cv_func_iconv_works=yes
gl_cv_func_wcwidth_works=yes
gt_cv_func_printf_posix=yes
gt_cv_int_divbyzero_sigfpe=yes
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --cache-file=config.cache \
    --disable-nls
make
#cp gettext-tools/gnulib-lib/.libs/libgettextlib.la{,i}
#cp gettext-tools/src/.libs/libgettextsrc.la{,i}
make DESTDIR=/gllfsc install
cd ..
rm -rf gettext-0.18.3.1
cd
exit 0
```

6.31 Grep

GNU `grep` command searches one or more input files for lines containing a match to a specified pattern.

```
su - grep
# 1 minute
tar xf /gllfsc/download/grep-2.15.tar.xz -C /gllfsc/build
cd /gllfsc/build/grep-2.15
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --bindir=/bin \
    --disable-perl-regexp \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf grep-2.15
cd
exit 0
```

Option `--disable-perl-regexp` disables support of Perl-style regular expressions (regexp).

6.32 Groff

Groff is the GNU version of the roff document formatting system which is used to produce man pages.

```
su - groff
# 2 minutes
tar xf /gllfsc/download/groff-1.22.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/groff-1.22.2
PAGE=A4 \
    ./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make \
    TROFFBIN=troff \
    GROFFBIN=groff \
    GROFF_BIN_PATH=
make prefix=/gllfsc install
ln -sv soelim /gllfsc/bin/zsoelim
ln -sv eqn /gllfsc/bin/geqn
ln -sv tbl /gllfsc/bin/gtbl
cd ..
rm -rf groff-1.22.2
cd
# man-db installs its own version of zsoelim:
mv -v /gllfsc/bin/zsoelim{,.groff}
exit 0
```

The variables `TROFFBIN=troff` and `GROFFBIN=groff` tell `make` to use `troff` and `groff` commands installed in the Chapter 5 [Building the Cross-Compilation Tools], page 25, to build documentation.

The variable `GROFF_BIN_PATH` before `PATH` is checked for programs `groff` is calling (preprocessors, `troff`, and output devices). If not set, it defaults to the directory where the `groff` binary is located.

The symlinks are used for compatibility.

6.33 Gzip

GNU Gzip is a data compression program.

```
su - gzip
# 1 minute
tar xf /gllfsc/download/gzip-1.6.tar.gz -C /gllfsc/build
cd /gllfsc/build/gzip-1.6
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf gzip-1.6
cd
exit 0
```

6.34 Inetutils

GNU Inetutils is a collection of common network programs.

```
su - inetutils
# 1 minute
tar xf /gllfsc/download/inetutils-2.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/inetutils-2.2
#sed -i '/gets is a security hole/d' lib/stdio.in.h
sed -i '/PATH_PROCNET_DEV/s/\ no//' paths
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make DESTDIR=/gllfsc install
cd ..
rm -rf inetutils-2.2
cd
# util-linux installs its own verion of logger:
mv -v /gllfsc/bin/logger{,.inetutils}
mv -v /gllfsc/usr/share/man/man1/logger.1{,.inetutils}
exit 0
```

'`sed -i '/PATH_PROCNET_DEV/s/\ no//' paths`' is used to fix the following error when issuing '`make`': '`'PATH_PROCNET_DEV' undeclared (first use in this function)`'.

6.35 Iproute2

Iproute2 is a collection of utilities for controlling TCP and UDP IP networking and traffic.

You need Bison and Flex on your system to compile this program from source.

```
su - iproute2
# 1 minute
tar xf /gllfsc/download/iproute2-3.10.0.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/iproute2-3.10.0
sed -i.orig '/^TARGETS/s@arpd@@g' misc/Makefile
make \
    DESTDIR=/gllfsc \
    CC="${CC}" \
    DOCDIR=/share/doc/iproute2 \
    MANDIR=/share/man
make \
    DESTDIR=/gllfsc \
    DOCDIR=/share/doc/iproute2 \
    MANDIR=/share/man \
    install
cd ..
rm -rf iproute2-3.10.0
cd
exit 0
```

'`sed -i.orig '/^TARGETS/s@arpd@@g' misc/Makefile`' is used to disable the build of `arpd` as it requires Berkeley DB to be installed.

`DOCDIR` and `MANDIR` indicate the location in which the documentation and the manual pages will be installed, respectively. Those are no absolute paths but use the value of `DESTDIR` as a prefix.

6.36 Kbd

Kbd contains keytable files and keyboard utilities.

You need Check on your system to compile this program from source.

```
su - kbd
# 1 minute
tar xf /gllfsc/download/kbd-2.0.1.tar.gz -C /gllfsc/build
cd /gllfsc/build/kbd-2.0.1

# Do not check for CHECK:
sed -i.orig '14s/^/#/' configure.ac
autoconf configure.ac > configure

./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-vlock \
    --disable-nls
sed -i.orig '/^SUBDIRS/s/ tests//' Makefile.in
make
make DESTDIR=/gllfsc install
cd ..
rm -rf kbd-2.0.1
cd
exit 0
```

'`sed -i.orig '/SUBDIRS/s/ tests//' Makefile.am`' is used to prevent files in the `tests` directory to be built.

Option `--disable-vlock` disables the build of vlock. vlock needs PAM library headers to be present on the build system and is not necessary for us, so we do not build it.

6.37 Kmod

Kmod (previously known as module-init-tools) provides userspace-side assistance in loading kernel modules and their dependencies.

```
su - kmod
# 1 minute
tar xf /gllfsc/download/kmod-15.tar.gz -C /gllfsc/build
cd /gllfsc/build/kmod-15
zlib_CFLAGS="-I/gllfsc/include" \
    zlib_LIBS="-L/gllfsc/lib -lz" \
    ./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --with-zlib \
    --disable-manpages
make
make \
    DESTDIR=/gllfsc \
    INSTALL=install \
    install
```

```
cd ..
rm -rf kmod-15
cd

# For bootscripts:
ln -sv kmod /gllfsc/bin/lsmod
ln -sv kmod /gllfsc/bin/depmod
ln -sv kmod /gllfsc/bin/insmod
ln -sv kmod /gllfsc/bin/modprobe
ln -sv kmod /gllfsc/bin/modinfo
ln -sv kmod /gllfsc/bin/rmmod

# Fix permissions for Package User util-linux:
chmod g+w,o+t /gllfsc/usr/share/bash-completion/completions

exit 0
```

'`zlib_CFLAGS`' and '`zlib_LIBS`' are defined to avoid the error message: '`The pkg-config script could not be found or is too old. Make sure it is in your PATH or set the PKG_CONFIG environment variable to the full path to pkg-config. Alternatively, you may set the environment variables zlib_CFLAGS and zlib_LIBS to avoid the need to call pkg-config.`'

`--with-zlib` enables support for modules compressed with zlib.

By default, installation uses `INSTALL=install-with-care` which checks if old utilities have not been destroyed. To avoid this check, we use `INSTALL=install`.

6.38 Less

Less is a file pager: it is used to view the content of a text file.

```
su - less
# 1 minute
tar xf /gllfsc/download/less-458.tar.gz -C /gllfsc/build
cd /gllfsc/build/less-458
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make prefix=/gllfsc install
cd ..
rm -rf less-458
cd
exit 0
```

6.39 Libpipeline

GNU Libpipeline is a C library for manipulating pipelines of subprocesses in a flexible and convenient way.

```
su - libpipeline
# 1 minute
tar xf /gllfsc/download/libpipeline-1.3.0.tar.gz -C /gllfsc/build
cd /gllfsc/build/libpipeline-1.3.0
```

```
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix=
make
make prefix=/gllfsc install
cd ..
rm -rf libpipeline-1.3.0
cd
# fix man-db's /lib/libpipeline.so: error adding symbols: File in
# wrong format
rm /gllfsc/lib/libpipeline.la
exit 0
```

6.40 Make

GNU `make` utility determines automatically which pieces of a large program need to be recompiled, and issues the commands to recompile them.

```
su - make
# 1 minute
tar xf /gllfsc/download/make-4.0.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/make-4.0
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf make-4.0
cd
exit 0
```

6.41 Man-db

Man-db is an implementation of the standard Unix documentation system accessed using the man command. It uses a Berkeley DB database in place of the traditional flat-text whatis databases.

```
su - man-db
# 1 minute
tar xf /gllfsc/download/man-db-2.6.7.1.tar.xz -C /gllfsc/build
cd /gllfsc/build/man-db-2.6.7.1
libpipeline_CFLAGS="-I/gllfsc/include" \
    libpipeline_LIBS="-L/gllfsc/lib -lpipeline" \
    ./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
```

```
cd ..
rm -rf man-db-2.6.7.1
cd

sed -i 's/#\(DEFINE.*pager.*\)less -s/\1 less -isRc/' \
    /gllfsc/etc/man_db.conf
exit 0
```

'`libpipeline_CFLAGS`' and '`libpipeline_LIBS`' are defined to avoid the error message: '`The pkg-config script could not be found or is too old. Make sure it is in your PATH or set the PKG_CONFIG environment variable to the full path to pkg-config. Alternatively, you may set the environment variables libpipeline_CFLAGS and libpipeline_LIBS to avoid the need to call pkg-config.`'

The `sed` command is used to replace default pager with `less`. Option `-c` will cause `less` to display man pages faster as this option disables scrolling. Option `-R` will cause `less` to render colors in the man pages.

6.42 Nano

GNU nano is a lightweight text editor.

```
su - nano
# 1 minute
tar xf /gllfsc/download/nano-2.3.2.tar.gz -C /gllfsc/build
cd /gllfsc/build/nano-2.3.2
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
sed -i.orig \
    '/CPPFLAGS/s@/usr/include/ncursesw@/gllfsc/include@' \
    `find . -iname 'Makefile'`
make
make DESTDIR=/gllfsc install
cd ..
rm -rf nano-2.3.2
cd
exit 0
```

The sed expression is used to replace `/usr/include/ncursesw` with `/gllfsc/include` in every file named `Makefile` in order to overcome the error '`/usr/include/ncursesw/ncurses.h:60:34: fatal error: ncursesw/ncurses_dll.h: No such file or directory`'.

> **Note:** commands in nano are displayed as in '^X'. The '^' character means `CTRL` key, so '^X' means *`CTRL-X`*: press *`CTRL`* and *`X`* keys simultaneously on the keyboard.

6.43 Patch

GNU patch takes a patch file containing a difference listing produced by the `diff` program and applies those differences to one or more original files, producing patched versions.

```
su - patch
# 1 minute
tar xf /gllfsc/download/patch-2.7.1.tar.bz2 -C /gllfsc/build
```

```
cd /gllfsc/build/patch-2.7.1
cat > config.cache << EOF
ac_cv_path_ed_PROGRAM=ed
ac_cv_func_strnlen_working=yes
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --cache-file=config.cache
make
make prefix=/gllfsc install
cd ..
rm -rf patch-2.7.1
cd
exit 0
```

6.44 Psmisc

This package contains utilities that use the proc filesystem.

```
su - psmisc
# 1 minute
tar xf /gllfsc/download/psmisc-22.20.tar.gz -C /gllfsc/build
cd /gllfsc/build/psmisc-22.20
cat > config.cache << EOF
ac_cv_func_malloc_0_nonnull=yes
ac_cv_func_realloc_0_nonnull=yes
EOF
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --cache-file=config.cache \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf psmisc-22.20
cd
exit 0
```

6.45 Shadow

```
su - shadow
# 1 minute
tar xf /gllfsc/download/shadow-4.6.tar.xz -C /gllfsc/build
cd /gllfsc/build/shadow-4.6
#automake
echo "ac_cv_func_setpgrp_void=yes" > config.cache
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
```

```
    --libdir=/lib \
    --sysconfdir=/etc \
    --enable-shared \
    --without-audit \
    --without-libpam \
    --without-selinux \
    --cache-file=config.cache \
    --disable-nls
sed -i.orig '/man_MANS/s/$(man_nopam) //' man/ru/Makefile
#sed -i.orig 's/groups$(EXEEXT) //' src/Makefile
#for mkf in $(find man -name Makefile)
#    do
#    sed -i.orig -e '/groups.1.xml/d' -e 's/groups.1 //' ${mkf}
#    done
make
make DESTDIR=/gllfsc install
sed -i.orig -e 's@#MD5_CRYPT_ENAB.no@MD5_CRYPT_ENAB yes@' \
    -e 's@/var/spool/mail@/var/mail@' \
    /gllfsc/etc/login.defs
#${CROSS_TARGET}-pwconv
#${CROSS_TARGET}-grpconv
cd ..
rm -rf shadow-4.6
cd
# util-linux installs its own version of nologin:
mv -v /gllfsc/bin/nologin{,.shadow}
mv -v /gllfsc/usr/share/man/man8/nologin.8{,.shadow}
# Adjusting PATH:
sed -i /PATH=/s,=.*$,=/local/bin:/bin, /gllfsc/etc/login.defs
exit 0
```

The option `--enable-man` is used to generate man pages.

The first call of `sed` removes *$(man_nopam)* on the line with man_MANS in `man/ru/Makefile.am` in order for '`make install`' to complete.

The second call of `sed` disables the build of command `groups`, as coreutils already installed it.

The last call of `sed` enables support for MD5 encrypted passwords and changes the mail default directory from `/var/spool/mail` to `/var/mail`.

6.46 Sysvinit

Sysvinit is the system-V style init process. Init is the first process started during booting. It is started by the kernel. Init continues running as a daemon until the system is shut down. It is the direct or indirect ancestor of all other processes and automatically adopts all orphaned processes.

```
su - sysvinit
# 1 minute
tar xf /gllfsc/download/sysvinit-2.88dsf.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/sysvinit-2.88dsf
sed -i.orig -e 's@/dev/initctl@$(ROOT)&@g' \
    -e 's@\(mknod \)-m \([0-9]* \)\(.* \)p@\1\3p; chmod \2\3@g' \
    -e '/^ifeq/s/$(ROOT)//' \
```

```
    -e 's@/usr/lib@$(ROOT)/lib@' \
    src/Makefile
make -C src clobber
make -C src ROOT=/gllfsc CC="${CC}"
make -C src ROOT=/gllfsc INSTALL="install" install
cd ..
rm -rf sysvinit-2.88dsf
cd

cat > /gllfsc/etc/inittab << EOF
# Begin /etc/inittab

id:3:initdefault:

si::sysinit:/etc/rc.d/init.d/rc sysinit

l0:0:wait:/etc/rc.d/init.d/rc 0
l1:S1:wait:/etc/rc.d/init.d/rc 1
l2:2:wait:/etc/rc.d/init.d/rc 2
l3:3:wait:/etc/rc.d/init.d/rc 3
l4:4:wait:/etc/rc.d/init.d/rc 4
l5:5:wait:/etc/rc.d/init.d/rc 5
l6:6:wait:/etc/rc.d/init.d/rc 6

ca:12345:ctrlaltdel:/sbin/shutdown -t1 -a -r now

su:S016:once:/sbin/sulogin

1:2345:respawn:/sbin/agetty --noclear tty1 9600
2:2345:respawn:/sbin/agetty tty2 9600
#3:2345:respawn:/sbin/agetty tty3 9600
#4:2345:respawn:/sbin/agetty tty4 9600
#5:2345:respawn:/sbin/agetty tty5 9600
#6:2345:respawn:/sbin/agetty tty6 9600

#c0:12345:respawn:/sbin/agetty 115200 ttyS0 vt100

# End /etc/inittab
EOF
# util-linux installs its own versions:
mv -v /gllfsc/bin/mountpoint{,.sysvinit}
mv -v /gllfsc/bin/sulogin{,.sysvinit}
mv -v /gllfsc/bin/mesg{,.sysvinit}
mv -v /gllfsc/bin/last{,.sysvinit}
mv -v /gllfsc/bin/utmpdump{,.sysvinit}
mv -v /gllfsc/bin/lastb{,.sysvinit}
mv -v /gllfsc/usr/share/man/man1/mesg.1{,.sysvinit}
mv -v /gllfsc/usr/share/man/man1/last.1{,.sysvinit}
mv -v /gllfsc/usr/share/man/man1/lastb.1{,.sysvinit}
mv -v /gllfsc/usr/share/man/man1/utmpdump.1{,.sysvinit}
mv -v /gllfsc/usr/share/man/man1/mountpoint.1{,.sysvinit}
mv -v /gllfsc/usr/share/man/man8/sulogin.8{,.sysvinit}
```

```
exit 0
```

The first call of `sed` replaces `/dev/initctl` with `$(ROOT)/dev/initctl`, and `/usr/lib` with `$(ROOT)/lib` among other things in order to install sysvinit on the target system.

'`make -C src clobber`' is used to clean up the `src` directory.

Then, we create the `inittab` file that describes which processes are started at bootup and during normal operation.

The line '`#c0:12345:respawn:/sbin/agetty 115200 ttyS0 vt100`' is commented out (with `#`) in order to avoid the message: '`INIT: Id "c0" respawning too fast: disabled for 5 minutes`' on the target system.

6.47 Tar

GNU tar is an archiving utility: it stores and extracts files from a tape or disk archive.

```
su - tar
# 1 minute
tar xf /gllfsc/download/tar-1.27.1.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/tar-1.27.1
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf tar-1.27.1
cd
exit 0
```

6.48 Texinfo

GNU Texinfo is a documentation system that can produce both online information and a printed manual from a single source.

You need Ncurses headers on your system to compile this program from source.

```
su - texinfo
# 1 minute
tar xf /gllfsc/download/texinfo-4.13a.tar.gz -C /gllfsc/build
cd /gllfsc/build/texinfo-4.13
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make -C tools/gnulib/lib
make -C tools
make
make DESTDIR=/gllfsc install
cd ..
rm -rf texinfo-4.13
cd
```

```
cd /gllfsc/share/info
#rm dir
for f in *
    do install-info $f dir 2>/dev/null
done
cd
exit 0
```

The first three calls of `make` make it possible to build Texinfo by cross-compilation.

For Info to work, the `info` directory must contain a file that serves as a top level directory for the Info system. By convention, this file is called `dir`. We update this file for the target system.

6.49 Udev

Udev is the dynamic device management of the kernel Linux.

You need Gperf on your system to compile this program from source. Under GLLFSC, do, as root:

```
tar xf /gllfsc/download/gperf-3.0.4.tar.gz
cd gperf-3.0.4
./configure --prefix=
make install
cd ..
rm -rf gperf-3.0.4
```

Then:

```
su - udev
# 1 minute
tar xf /gllfsc/download/udev-175.tar.gz -C /gllfsc/build
cd /gllfsc/build/udev-175
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --with-rootlibdir=/lib \
    --libexecdir=/lib/udev \
    --docdir=/share/doc/udev-175 \
    --disable-introspection \
    --with-pci-ids-path=no \
    --with-usb-ids-path=no \
    --disable-gudev
make
make DESTDIR=/gllfsc install
install -dv /gllfsc/lib/firmware
ln -sv ../lib/udev/udevd /gllfsc/sbin/udevd
cd ..
rm -rf udev-175
cd

# fix /lib/libudev.so: error adding symbols: File in wrong format
rm /gllfsc/lib/libudev.la

# Fix /bin/install: cannot change permissions of
```

```
# '/gllfsc/lib/udev/devices/pts': No such file or directory
chmod g+w,o+t /gllfsc/lib/udev/devices

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/lib/udev/rules.d
chmod g+w,o+t /gllfsc/share/gtk-doc
chmod g+w,o+t /gllfsc/share/gtk-doc/html
chmod g+w,o+t /gllfsc/share/pkgconfig

exit 0
```

6.50 Util-Linux

util-linux is a random collection of utilities for use with the kernel Linux.

> **Warning:** If you have trouble building util-linux from a distribution using .deb packages, try to uninstall the package named '`libtinfo-dev`'. Then remove `/gllfsc/build/util-linux-2.24` and build it again.

```
su - util-linux
# 3 minutes
tar xf /gllfsc/download/util-linux-2.24.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/util-linux-2.24
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --enable-partx \
    --disable-wall \
    --enable-write \
    --disable-makeinstall-chown \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -r util-linux-2.24
cd
# procps-ng installs its own version of kill:
mv -v /gllfsc/bin/kill{,.util-linux}
mv -v /gllfsc/usr/share/man/man1/kill.1{,.util-linux}
exit 0
```

Option `--enable-partx` enables the build and installation of the `addpart`, `delpart` and `partx` commands.

Option `--disable-wall` disables the build of the `wall` command which is already provided by sysvinit.

Option `--enable-write` enables the build and installation of the `write` command.

Option `--disable-makeinstall-chown` disables the change of owner to root for installed programs.

6.51 XZ-Utils

XZ Utils is a general-purpose data compression software with high compression ratio.

```
su - xz-utils
# 1 minute
```

```
tar xf /gllfsc/download/xz-5.0.8.tar.bz2 -C /gllfsc/build
cd /gllfsc/build/xz-5.0.8
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
make
make DESTDIR=/gllfsc install
cd ..
rm -rf xz-5.0.8
cd
exit 0
```

6.52 Bootscripts

The bootscript archive contains scripts that manage services during system's bootup and shutdown.

```
su - bootscripts
# 1 minute
tar xf /gllfsc/download/bootscripts-cross-lfs-2.0.0.tar.xz \
    -C /gllfsc/build
cd /gllfsc/build/bootscripts-cross-lfs-2.0-pre2
make DESTDIR=/gllfsc install-bootscripts
make DESTDIR=/gllfsc install-network
cd ..
rm -rf bootscripts-cross-lfs-2.0-pre2
cd

# We do not use a system log daemon:
rm /gllfsc/etc/rc.d/rc3.d/S10rsyslog

# Bringing up network interfaces fails:
rm /gllfsc/etc/rc.d/rc3.d/S20network

# Fix permissions for Package Users:
chmod g+w,o+t /gllfsc/etc/sysconfig

exit 0
```

This installs basic bootscripts required for bootup and shutdown, and network-related bootscripts.

> **Note:** To modify the keyboard layout at boot, for instance fr' azerty:
>
> ```
> sed -i.orig '/^KEYMAP/s/us/fr/' /gllfsc/etc/sysconfig/i18n
> ```

6.53 The Kernel

Linux is a kernel aimed towards POSIX and Single UNIX Specification compliance.

You need Bc and Lzma on your system to compile this program from source. Under GLLFSC, install ed, which is a bc dependency then bc:

```
tar xf /gllfsc/download/ed-1.1.tar.bz2
cd ed-1.1
```

```
./configure --prefix=
make install
cd ..
rm -rf ed-1.1

tar xf /gllfsc/download/bc-1.07.1.tar.gz
cd bc-1.07.1
./configure --prefix=
make install
cd ..
rm -rf bc-1.07.1
su - linux-libre
# 25 minutes
tar xf /gllfsc/download/linux-libre-3.10.108-gnu.tar.xz \
    -C /gllfsc/build
cd /gllfsc/build/linux-3.10.108
make mrproper
```

Then:

```
cp arch/x86/configs/x86_64_defconfig .config
#patch -Np1 -i /gllfsc/download/100gnu+freedo.patch
```

Then, if you want to change the configuration:

```
make ARCH=x86_64 CROSS_COMPILE=${CROSS_TARGET}- menuconfig
```

Note: In order to avoid the error message "cannot create directory '/dev/pts': read only filesystem" at boot, you have to activate the two options below:

```
Device Drivers
> Generic Driver Options
  > [*] Maintain a devtmpfs fs to mount on /dev
  > [*] Automount devtmpfs at /dev, after the kernel mounted the rootfs
```

Also ensure you have CONFIG_DRM_I915_KMS=y in your .config after the configuration step, working under tty is more pleasant with a nice resolution:

```
Device Drivers
> Graphics support
  > <*> Direct Rendering Manager (XFree86 4.1.0 and higher DRI support)
  > <*> Intel 8xx/9xx/G3x/G4x/HD Graphics
  > [*] Enable modesetting on intel by default
```

Disable the Tux/Freedo logo with:

```
Device Drivers
> Graphics support
  > [ ] Bootup logo
```

Enable Ethernet driver for Lenovo X200 (Intel 82567LM):

```
Device Drivers
> Network device support
  > Ethernet driver support
    > Intel (R) PRO/1000 PCI-Express Gigabit Ethernet support
```

Then:

```
make \
    ARCH=x86_64 \
    CROSS_COMPILE=${CROSS_TARGET}-
```

```
make \
    ARCH=x86_64 \
    CROSS_COMPILE=${CROSS_TARGET}- \
    INSTALL_MOD_PATH=/gllfsc \
    modules_install
cp arch/x86/boot/bzImage /gllfsc/boot/vmlinuz-3.10.108-gnu
cp System.map /gllfsc/boot/System.map-3.10.108-gnu
cp .config /gllfsc/boot/config-3.10.108-gnu
cd ..
cd
exit 0
```

Tip: because future compilation may need kernel sources, the compilation directory of the kernel should be preserved.

6.54 GRUB

GNU GRUB is a Multiboot boot loader.

A bootloader is the first software program that runs when a computer starts. It is responsible for loading and transferring control to the operating system kernel software (such as Linux). The kernel, in turn, initializes the rest of the system (e.g. GNU).

```
su - grub
# 3 minutes
tar xf /gllfsc/download/grub-2.00.tar.gz \
    -C /gllfsc/build
cd /gllfsc/build/grub-2.00
sed -i '/gets is a security hole/d' grub-core/gnulib/stdio.in.h
./configure \
    --build=${CROSS_HOST} \
    --host=${CROSS_TARGET} \
    --prefix= \
    --disable-nls
cd grub-core/script
EXP1='\n#pragma GCC diagnostic ignored \"-Wunused-function\"'
sed -i.1 '/Wunsafe-loop-optimizations\"/s,$,'"$EXP1"',' yylex.l
EXP2='\n#pragma GCC diagnostic ignored \"-Wsign-compare\"'
sed -i.2 '/Wunused-function\"/s,$,'"$EXP2"',' yylex.l
cd ../..
make
make DESTDIR=/gllfsc install
cd ..
rm -rf grub-2.00
cd

mkdir /gllfsc/boot/grub

# Fix permissions for Package Users:
chmod g+w,o+t /etc/bash_completion.d

exit 0
```

'`sed -i '/gets is a security hole/d' grub-core/gnulib/stdio.in.h`' is used to fix the following error when issuing '`make`':

```
./stdio.h:456:1: error: 'gets' undeclared here (not in a function)
make[4]: Leaving directory '/gllfsc/build/grub-2.00/grub-core/gnulib'
```

The sed expressions applied to yylex.l fixes:

```
grub_script.yy.c:2296:17: error: comparison between signed and
unsigned integer expressions [-Werror=sign-compare]
./grub-core/script/yylex.l
```

7 Creating Required Configuration Files for the New System

7.1 File for Time Setup

```
su - bootscripts
echo UTC=1 > /gllfsc/etc/sysconfig/clock

# If you have trouble with the clock behaviour, do:
mv -v /gllfsc/etc/rc.d/rcsysinit.d/{S15setclock,K15setclock}
exit 0
```

7.2 Setting up Keyboard Function keys for the Shell

Note: You can automate this section by splitting the file `gllfsc-core2-1.9.1.texi` into instructions:

```
csplit gllfsc-core2-1.9.1.texi '/su - readline/' '{*}'
mv xx03 7.2
chmod o+x 7.2
```

Then, with '`nano`', you can remove the line beginning with '`su -`', and add the line '`set -e`' and the line '`set -v`' at the beginning of the script so that it will exit on error and print each instruction before executing it:

```
nano 7.2
```

Then, once inside the readline User personal directory:

```
/root/7.2
```

Readline default configuration file is set:

```
su - readline
cat > /gllfsc/etc/inputrc << EOF
set bell-style none
set convert-meta Off
set horizontal-scroll-mode Off
set input-meta On
set output-meta On
"\eOd": backward-word
"\eOc": forward-word
"\e[1~": beginning-of-line
"\e[4~": end-of-line
"\e[5~": beginning-of-history
"\e[6~": end-of-history
"\e[3~": delete-char
"\e[2~": quoted-insert
"\eOH": beginning-of-line
"\eOF": end-of-line
"\e[H": beginning-of-line
"\e[F": end-of-line
EOF
exit 0
```

If `convert-meta` is set to '`On`', Readline will convert characters with the eighth bit set to an ASCII key sequence by stripping the eighth bit and prefixing an `ESC` character, converting them to a meta-prefixed key sequence.

`horizontal-scroll-mode` set to '`Off`' means that the text of the lines being edited will be wrapped onto a new screen line when they are longer than the width of the screen, instead of being scrolled horizontally on a single screen line.

If `input-meta` is set to '`On`', Readline will enable eight-bit input (it will not clear the eighth bit in the characters it reads), regardless of what the terminal claims it can support.

If `output-meta` is set to '`On`', Readline will display characters with the eighth bit set directly rather than as a meta-prefixed escape sequence.

7.3 Setting up Bash Shell Startup Files

```
su - bash
cat > /gllfsc/etc/profile << 'EOF'
export LANG=en_US.UTF-8
export INPUTRC=/etc/inputrc
export PS1='\[\e[31m\]\A-\W\[\e[00m\]# '
EOF
exit 0
```

The environment variable `LANG` defines the default language that should be used on the system. '`en_US.UTF-8`' means "english" language, country "US" and UTF-8 (UCS Transformation Format—8-bit) encoding (Unicode).

For explanations on `PS1`, see Section 3.5 [Environment Variables Setup], page 9.

7.4 Localhost Setup

```
su - bootscripts
echo HOSTNAME=gllfsc > /gllfsc/etc/sysconfig/network
exit 0
```

7.5 Setting up `hosts` File

```
echo "127.0.0.1 gllfsc localhost" > /gllfsc/etc/hosts
```

7.6 Setting up Network Address

You can choose to have a network static or dynamic address.

7.6.1 Setting up Network Static Address

```
su - bootscripts
cd /gllfsc/etc/sysconfig/network-devices
mkdir -v ifconfig.eth0
cat > ifconfig.eth0/ipv4 << EOF
ONBOOT=yes
SERVICE=ipv4-static
IP=192.168.1.1
GATEWAY=192.168.1.2
PREFIX=24
BROADCAST=192.168.1.255
EOF
cd
exit 0
```

Warning: `IP`, `GATEWAY`, `BROADCAST` addresses are set up according to one's situation.

7.6.2 Setting up Network Dynamic Address

```
su - bootscripts
cd /gllfsc/etc/sysconfig/network-devices
mkdir -v ifconfig.eth0
cat > ifconfig.eth0/dhcpcd << EOF
ONBOOT=yes
SERVICE=dhcpcd
DHCP_START="-q"
DHCP_STOP="-k"
EOF
cd
exit 0
```

7.7 Setting up DNS

```
cat > /gllfsc/etc/resolv.conf << EOF
nameserver your-main-DNS-address
nameserver your-secondary-DNS-address
EOF
```

7.8 `fstab` File Creation

The file `/etc/fstab` is used at boot to mount partitions under the requested directories.

```
su - util-linux
cat > /gllfsc/etc/fstab << EOF
# file system    mount-point  type     options         dump  fsck order

/dev/sda3        /            ext3     defaults         0    0
#/dev/sda7        /home        ext3     defaults         0    0
/dev/sda5        swap         swap     pri=1            0    0
devtmpfs         /dev         dev      defaults         0    0
proc             /proc        proc     defaults         0    0
tmpfs            /run         run      defaults         0    0
sysfs            /sys         sysfs    defaults         0    0
devpts           /dev/pts     devpts   gid=4,mode=620   0    0
shm              /dev/shm     tmpfs    defaults         0    0
EOF
exit 0
```

Warning: the name of the hard drive and the filesystems used here have to be modified to reflect *your* real situation.

8 Before Booting GLLFSC

8.1 Enabling Package Users on the target GLLFSC

Note: You can automate parts of this chapter by splitting the file `gllfsc-core2-1.9.1.texi` into instructions for each section:

```
csplit gllfsc-core2-1.9.1.texi '/chown shadow/' '{*}'
rm xx0[0-5]
mv xx06 8.1
csplit 8.1 '/Archiving the System/'
mv xx00 8.1
mv xx01 8.2
csplit 8.2 '/Some Recommendations/'
mv xx00 8.2
rm xx01
```

Then, with '`nano`', you can add the line '`set -e`' and the line '`set -v`' at the beginning of each script so that it will exit on error and print each instruction before executing it. Then, edit its content. Then, make files executable and execute them:

```
chmod u+x 8.1 8.2
./8.1
./8.2
```

In order to enable Package Users under GLLFSC, we need to copy the package users and groups to the new system:

```
chown shadow:install /gllfsc/etc/{passwd,group}
su - shadow
grep ':100' /etc/passwd >> /gllfsc/etc/passwd
grep ':100' /etc/group >> /gllfsc/etc/group
exit 0
```

Then, as root, download Package Users archive at `https://www.linuxfromscratch.org/hints/downloads/files/ATTACHMENTS/more_control_and_pkg_man/more_control_helpers.tar.bz2` inside `/gllfsc/download`. :

```
cp -av /usr/src/* /gllfsc/usr/src

cd /tmp
tar xf /gllfsc/download/more_control_helpers.tar.bz2
cd more_control_helpers
rm sbin/{groupadd,useradd}

mkdir -v /gllfsc/etc/pkgusr
rm -v etc/{build,skel-package/{build,build.conf,.project}}
cp -Rv etc/* /gllfsc/etc/pkgusr

mkdir -v /gllfsc/usr/lib/pkgusr
cp -Rv lib/* /gllfsc/usr/lib/pkgusr

cp -v bin/* /gllfsc/usr/bin

sed -i.orig 's/"\$1"$/"install"/' sbin/install_package

cp -v sbin/{add_package_user,install_package} /gllfsc/usr/sbin
```

```
sed -i '/GROUP=1000/s/^/#/' /gllfsc/etc/default/useradd
sed -i '/CREATE_MAIL_SPOOL/s/yes/no/' /gllfsc/etc/default/useradd
```

Then:

```
cat > /gllfsc/etc/pkgusr/bash_profile << 'EOF'
export PATH=/usr/lib/pkgusr:/bin:/local/bin

# Make prompt reflect that we are a package user.
export PROMPT_COMMAND='PS1="\[\e[35m\]\A-package \u:\W\[\e[00m\]> "'

# Go to the home directory whenever we su to a package user.
cd

alias less='less -ic'
EOF
```

Finally:

```
cat > /gllfsc/root/.bash_profile << EOF
# Tab-complete package users when using su, finger or pinky
complete -o default -o nospace -A user su finger pinky
EOF
```

8.2 Archiving the System

Create required files:

```
cd /gllfsc
mknod -m 600 dev/console c 5 1
mknod -m 666 dev/null c 1 3
cp -av dev/{console,null} lib/udev/devices/
```

We archive the entire system by using the following command:

```
mkdir build.orig
mv build/linux-3.10.108 build.orig

# 7 minutes
tar -cjf gllfsc-core2-1.9.1.tar.bz2 \
    bin boot build dev download etc home include lib* local man mnt \
    opt proc root run sbin service share src static sys tmp usr var

cd
```

It is then simple to copy `gllfsc-core2-1.9.1.tar.bz2` to the target machine and extract it.

> **Warning:** If you use another GLLFSC system when you extract `gllfsc-core2-1.9.1.tar.bz2` to its dedicated partition, you should use option '`--numeric-owner`' to avoid conflicts with Package User names.

8.3 Some Recommendations

We recommend extracting the system to an empty partition. Moreover, the filesystem of the chosen partition has to be a filesystem supported by the kernel you compiled. Finally, this partition has to be consistent with the system description in the file `/etc/fstab` you created during setup (see Section 7.8 [fstab File Creation], page 67).

Then, you will have to edit the GRUB configuration file of the target machine: `/boot/grub/grub.cfg`. You can do it with '`nano`'.

A minimal `/boot/grub/grub.cfg` for classical hard disk could be:

```
insmod ext2
set default=0
set timeout=5

menuentry 'GLLFSC 1.9.1' {
    echo 'Loading linux-libre-3.10.108-gnu...'
    linux (hd0,3)/boot/vmlinuz-3.10.108-gnu root=/dev/sda3 quiet
}
```

A minimal `/boot/grub/grub.cfg` for hard disk supporting AHCI (Advanced Host Controller Interface) could be:

```
insmod part_msdos
insmod ext2
set default=0
set timeout=5

menuentry 'GLLFSC 1.9.1' {
    echo 'Loading linux-libre-3.10.108-gnu...'
    linux (ahci0,msdos3)/boot/vmlinuz-3.10.108-gnu root=/dev/sda3 quiet
}
```

8.4 Halting the Computer

In order to halt the computer, type:

```
init 0
```

If you prefer to reboot instead type:

```
init 6
```

9 After Booting GLLFSC

Some system configuration and package installation can only be made after booting onto the new system. The build process of this chapter takes about 25 minutes on my Lenovo ThinkPad X200.

9.1 Boot Process

Once the computer starts, the BIOS makes GRUB responsible for loading and transferring control to the operating system kernel (Linux-libre here). The kernel, in turn, initializes the rest of the operating system, beginning with init (runit at the end of this chapter).

If, for some reason, GRUB fails to launch linux-libre, you may be presented the following prompt:

```
grub rescue >
```

In this case, you may launch GRUB by issuing the following commands:

```
set
ls
# If you want to boot the kernel on partition 1 of a classical drive:
set prefix=(hd0,1)/grub
set root=(hd0,1)
insmod normal
normal
```

9.2 Login

To login as *root*, just type '`root`' when the system asks for your '`login:`'. There is no password.

Then, if you want to use the french keyboard layout, type '`loadkeys -q fr`'.

Note: To modify the keyboard layout at boot, for instance fr' azerty:

```
sed -i.orig '/^KEYMAP/s/us/fr/' /etc/sysconfig/i18n
```

9.3 Locales

You may want to have your new system display messages in your native language. If you desire to have a system supporting US english (german, french and China mainland's chinese are commented):

```
su - glibc
mkdir /lib/locale

#localedef -i de_DE -f UTF-8 de_DE
localedef -i en_US -f UTF-8 en_US
#localedef -i fr_FR -f UTF-8 fr_FR
#localedef -i zh_CN -f UTF-8 zh_CN
exit 0
```

Other locales are available:

- For available charmaps, see the content of `/share/i18n/charmaps`.
- For available locales, see the content of `/share/i18n/locales`.

9.4 Libevent

Note: You can automate parts of this chapter by splitting the script `3-build-post-boot.sh` (see Chapter 4 [Building the Cross-Compilation Toolchain], page 17) into instructions for each Package User:

```
csplit 3-build-post-boot.sh '/su -/' '{*}'
rm xx00 xx01 xx02 xx03
mv xx04 9.4-libevent
mv xx05 9.5-tmux
mv xx06 9.6-tz
mv xx07 9.7-runit
mv xx08 9.8-perl
mv xx09 9.9-openssl
mv xx10 9.10-wpa-supplicant
mv xx11 9.11-wireless-tools
mv xx12 9.12-wget
mv xx13 9.13-libtasn1
mv xx14 9.14-lynx
mv xx15 9.15-ca-certificates

csplit xx16 '/inetutils/'
mv xx00 9.16-procps-ng
rm xx16
mv xx01 xx99
csplit xx99 '/cat/'
rm xx99

mv xx01 xx99
csplit xx99 '/Clean up/'
mv xx00 9.17-pkgusr
mv xx01 9.18-archiving
rm xx99

chmod o+x 9.*
chmod u+x 9.17-pkgusr
```

Then, with '`nano`', you can remove lines beginning with '`su -`' and add the line '`set -e`' and the line '`set -v`' at the beginning of each script so that it will exit on error and print each instruction before executing it. To automate this step:

```
sed -i 's,su -.*,set -e\nset -v\n,' 9.*
```

You still have to add '`set -e`' and '`set -v`' at the begining of `9.16-pkgusr` and `9.17-archiving`, and '`exit 0`' at their end. Then, once inside the, for instance, tz User personal directory:

```
/root/9.4-libevent
```

Libevent is a dependency of Tmux.

```
su - libevent
# 1 minute
tar xf /download/libevent-2.0.22-stable.tar.gz -C /build
cd /build/libevent-2.0.22-stable
./configure \
    --prefix= \
    --disable-openssl
```

```
make
make DESTDIR= install
cd ..
rm -rf libevent-2.0.22-stable
cd
exit 0
```

9.5 Tmux

Tmux is a terminal multiplexer: it allows multiple terminal sessions to be accessed simultaneously in a single window.

```
su - tmux
# 1 minute
tar xf /download/tmux-1.8.tar.gz -C /build
cd /build/tmux-1.8
./configure --prefix=
make
make DESTDIR= install
cd ..
rm -rf tmux-1.8
cd
exit 0
```

9.6 Timezone

In order to have the time and date corresponding to the area where you live, you should build tzcode, tzdata and define your timezone.

```
su - tz
# 1 minute
mkdir /build/tz
tar xf /download/tzcode2013h.tar.gz -C /build/tz
tar xf /download/tzdata2013h.tar.gz -C /build/tz
cd /build/tz

make \
    TOPDIR=/ \
    TZDIR=/share/zoneinfo \
    ETCDIR=/bin

for TZ in africa antarctica asia australasia europe northamerica \
          southamerica pacificnew etcetera backward systemv factory \
          solar87 solar88 solar89; do
    zic -y "sh yearistype.sh" \
        -d /share/zoneinfo \
        -L /dev/null $TZ
done

zic -y "bash yearistype.sh" \
    -d /share/zoneinfo \
    -l GMT \
    -p America/New_York
```

```
cp iso3166.tab zone.tab /share/zoneinfo
cd ..
rm -rf tz
cd
```

Then, we define our timezone, in my case `Europe/Paris`:

```
cp -v --remove-destination \
    /share/zoneinfo/Europe/Paris \
    /etc/localtime
exit 0
```

9.7 Runit

runit is a cross-platform Unix init scheme with service supervision, a replacement for sysvinit, and other init schemes.

```
su - runit
# 1 minute
tar xf /download/runit-2.1.2.tar.gz -C /build
cd /build/admin/runit-2.1.2
cd src
make
make check

install -s -m0755 \
    chpst runit runit-init runsv runsvchdir runsvdir sv svlogd utmpset \
    /sbin

install -m0644 ../man/* \
    /share/man/man8

cd ..

mkdir /etc/runit

cp etc/debian/ctrlaltdel /etc/runit/

cd ../..
rm -rf admin
cd
```

The init-related programs have been installed. We need to create the boot scripts too: `/etc/runit/1` to boot the system, `/etc/runit/2` to launch 2 ttys and the service logging daemon and `/etc/runit/3` to halt or reboot the system.

```
cat > /etc/runit/1 << 'EOF'
#!/bin/sh
# system one time tasks

# Exit on error:
set -e

PATH=/bin

echo -n '16. Mounting kernel-based file systems:'
```

```
echo -n ' /proc'
mount -n -o nosuid,noexec,nodev -t proc proc /proc
echo -n ' /sys'
mount -n -o nosuid,noexec,nodev -t sysfs sys /sys
echo ' /run'
mount -n -o mode=0755,nosuid,nodev -t tmpfs run /run

echo -n '15. Creating directories:'
echo -n ' /run/lock'
mkdir -m 1777 /run/lock
echo -n ' /dev/pts'
mkdir -p /dev/pts
echo ' /dev/shm'
mkdir -p /dev/shm

echo '14. Mounting root file system in read-write mode.'
mount -n -o remount,rw / >/dev/null

# Remove fsck-related system watermarks.
rm -f /fastboot /forcefsck

echo '13. Recording existing mounts in /etc/mtab.'
> /etc/mtab
mount -f /
mount -f /proc
mount -f /sys
mount -f /run
mount -f /dev

echo '12. Mounting remaining file systems.'
mount -a -r >/dev/null

echo '11. Cleaning file system /tmp.'
cd /tmp && find . -xdev -mindepth 1 ! -name lost+found -delete

echo '10. Creating /var/run/utmp.'
if grep -q '^utmp:' /etc/group; then
    chmod 664 /var/run/utmp
    chgrp utmp /var/run/utmp
fi

echo '9. Starting udevd...'
echo '' > /sys/kernel/uevent_helper

/lib/udev/udevd --daemon

echo '8. Performing Coldplugging...'
/sbin/udevadm trigger --action=add --type=subsystems
/sbin/udevadm trigger --action=add --type=devices

/sbin/udevadm settle
```

```
# Uncomment the following lines if you use a swap partition:
#echo '7. Activating all swap files/partitions...'
#swapon -a

echo '6. Setting Font...'
setfont LatArCyrHeb-16 -C /dev/tty1
setfont LatArCyrHeb-16 -C /dev/tty2

echo '5. Setting keymap to UTF-8...'
dumpkeys | loadkeys --unicode

echo '4. Enabling Multibyte input...'
kbd_mode -u

echo '3. Setting up US Keymap...'
loadkeys -q us

echo '2. Setting encoding to UTF-8...'
echo -ne $'\033%G' > /dev/tty1
echo -ne $'\033%G' > /dev/tty2

echo '1. Bringing up the loopback interface...'
ip addr add 127.0.0.1/8 label lo dev lo
ip link set lo up

echo '0. Setting hostname to gllfsc...'
hostname gllfsc

echo
echo To login, remember:
echo your login is root
echo with no password
echo
echo You can now login here.
echo
echo If needed, you can use tty2 by pressing simultaneously Ctrl, Alt
echo and F2 keys. You can then come back to this screen \(tty1\) by
echo pressing simultaneously Ctrl, Alt and F1 keys.
echo
echo You can also use tmux to have multiple frames in a single window
echo Hotkeys:
echo CTRL-B then %
echo CTRL-B then \"
echo CTRL-B then LEFT, RIGHT, UP or DOWN ARROW
echo
echo Edit /etc/runit/1 if you want to remove this message.
echo

touch /etc/runit/stopit
chmod 0 /etc/runit/stopit

exit 0
```

```
EOF

chmod +x /etc/runit/1
cat > /etc/runit/2 << EOF
#!/bin/sh

PATH=/bin

exec env -i PATH=/bin \
runsvdir -P /service 'log: ........................................'
EOF

chmod +x /etc/runit/2
cat > /etc/runit/3 << EOF
#!/bin/sh

# Exit on error:
set -e

exec 2>&1

PATH=/bin

echo '4. Waiting for services to stop...'
sv down /service/*

echo '3. Exiting services...'
sv exit /service/*

echo '2. Deactivating all swap files/partitions...'
swapoff -a

# Unmount everything but /:
echo -n '1. Unmounting filesystems: /home'
umount -r /home
echo -n ' /proc'
umount -r /proc
echo -n ' /sys'
umount -r /sys
echo -n ' /dev/pts'
umount -r /dev/pts
echo ' /dev/shm'
umount -r /dev/shm

echo '0. Shutdown...'

exit 0
EOF

chmod +x /etc/runit/3
```

We now create useful services:

```
mkdir /etc/sv
mkdir /etc/sv/getty-1

cat > /etc/sv/getty-1/run << EOF
#!/bin/sh
exec /sbin/agetty --noclear tty1 9600
EOF
chmod +x /etc/sv/getty-1/run

cat > /etc/sv/getty-1/finish << EOF
#!/bin/sh
exec utmpset -w tty1
EOF
chmod +x /etc/sv/getty-1/finish

ln -sv /etc/sv/getty-1 /service/getty-1


mkdir -p /etc/sv/getty-2

cat > /etc/sv/getty-2/run << EOF
#!/bin/sh
exec /sbin/agetty tty2 9600
EOF
chmod +x /etc/sv/getty-2/run

cat > /etc/sv/getty-2/finish << EOF
#!/bin/sh
exec utmpset -w tty2
EOF
chmod +x /etc/sv/getty-2/finish

ln -sv /etc/sv/getty-2 /service/getty-2


mkdir /etc/sv/svlogd

cat > /etc/sv/svlogd/run << EOF
#!/bin/sh
exec svlogd
EOF
chmod +x /etc/sv/svlogd/run

ln -sv /etc/sv/svlogd /service/svlogd
exit 0
```

Finally, as root, make runit the default init:

```
mv /sbin/init /sbin/init.sysv
ln -sv runit-init /sbin/init
```

9.8 Perl

Perl is a high-level programming language.

Note: You may have to type '`exit`' twice during the configure phase of the Perl installation.

```
su - perl
# 10 minutes
tar xf /download/perl-5.18.1.tar.gz -C /build
cd /build/perl-5.18.1
sh Configure -ds -e -Dprefix=
make
make install
cd ..
rm -rf perl-5.18.1
cd

# Fix permissions for Package Users:
chmod g+w,o+t /local/lib/perl5/site_perl/5.18.1
chmod g+w,o+t /local/lib/perl5/site_perl/5.18.1/x86_64-linux
chmod g+w,o+t /local/lib/perl5/5.18.1/x86_64-linux

exit 0
```

9.9 OpenSSL

OpenSSL is a toolkit implementing the Transport Layer Security (TLS) and Secure Sockets Layer (SSL) protocols as well as a cryptography library.

```
su - openssl
# 5 minutes
tar xf /download/openssl-1.1.1.tar.gz -C /build
cd /build/openssl-1.1.1
./config \
    --prefix=/usr \
    --openssldir=/etc/ssl \
    shared
make -j1
# Install without the documentation:
make install_sw
cd ..
rm -rf openssl-1.1.1
cd
exit 0
```

9.10 Wpa_supplicant

Wpa_supplicant is a user space IEEE 802.1X/WPA supplicant (wireless client) for many wireless drivers.

```
su - wpa-supplicant
# 1 minute
tar xf /download/wpa_supplicant-2.7.tar.gz -C /build
cd /build/wpa_supplicant-2.7/wpa_supplicant

cat > .config << EOF
CONFIG_DRIVER_HOSTAP=y
CONFIG_DRIVER_WEXT=y
```

```
#CONFIG_DRIVER_NL80211=y
#CONFIG_DRIVER_WIRED=y

#CONFIG_PKCS12=y
#CONFIG_SMARTCARD=y

CONFIG_CTRL_IFACE=y

CONFIG_BACKEND=file
CONFIG_PEERKEY=y
#CONFIG_IEEE80211W=y

CONFIG_TLS=openssl

#CONFIG_IEEE80211N=y
EOF

sed -i.orig 's@local/@@g' Makefile
make
make install
cd ../..
rm -rf wpa_supplicant-2.7
cd

cat > /etc/wpa_supplicant.conf << EOF
network={
    ssid="MYESSID"
    key_mgmt=WPA-PSK
    pairwise=TKIP
    group=TKIP
    psk="MYPASSWORD"
}
EOF
chmod 600 /etc/wpa_supplicant.conf
exit 0
```

9.11 Wireless_tools

The Wireless Tools is a set of tools allowing to manipulate the Wireless Extensions.

```
su - wireless-tools
# 1 minute
tar xf /download/wireless_tools.29.tar.gz -C /build
cd /build/wireless_tools.29
make
make PREFIX= install
cd ..
rm -rf wireless_tools.29
cd
exit 0
```

9.12 Wget

GNU wget is an utility for downloading network data.

```
su - wget
# 1 minute
tar xf /download/wget-1.19.5.tar.gz -C /build
cd /build/wget-1.19.5
#sed -i.orig 's/item $thing/item C<$thing>/' doc/texi2pod.pl
OPENSSL_CFLAGS='-I/include/openssl' \
    OPENSSL_LIBS='-L/lib -lssl -lcrypto' \
    ./configure \
    --prefix= \
    --with-ssl=openssl \
    --disable-nls
make
make install
cd ..
rm -rf wget-1.19.5
cd
exit 0
```

'`OPENSSL_CFLAGS`' and '`OPENSSL_LIBS`' are defined to avoid the error message:

```
The pkg-config script could not be found or is too old. Make sure it
is in your PATH or set the PKG_CONFIG environment variable to the full
path to pkg-config. Alternatively, you may set the environment
variables OPENSSL_CFLAGS and OPENSSL_LIBS to avoid the need to call
pkg-config.
```

9.13 Libtasn1

GNU libtasn1 is a ASN.1 library.

```
su - libtasn1
# 1 minute
tar xf /download/libtasn1-3.4.tar.gz -C /build
cd /build/libtasn1-3.4
./configure --prefix=
make
make install
cd ..
rm -rf libtasn1-3.4
cd
exit 0
```

9.14 Lynx

Lynx is a text web browser.

```
su - lynx
# 2 minutes
tar xf /download/lynx2.8.9rel.1.tar.bz2 -C /build
cd /build/lynx2.8.9rel.1
./configure \
    --prefix= \
    --with-ssl=/lib \
```

```
    --enable-nls \
    --with-screen=ncursesw
make
make install
cd ..
rm -rf lynx2.8.9rel.1

# Stop asking questions about certificates:
sed -i s/#FORCE_SSL_PROMPT:PROMPT/FORCE_SSL_PROMPT:yes/ \
    /etc/lynx.cfg

# Display non-ascii characters:
sed -i s/#CHARACTER_SET:iso-8859-1/CHARACTER_SET:utf-8/  \
    /etc/lynx.cfg

# I don't want cookies:
sed -i 's/#SET_COOKIES:TRUE/SET_COOKIES:FALSE/'  \
    /etc/lynx.cfg
sed -i 's/#ACCEPT_ALL_COOKIES:FALSE/ACCEPT_ALL_COOKIES:FALSE/'  \
    /etc/lynx.cfg
sed -i 's/#PERSISTENT_COOKIES:FALSE/PERSISTENT_COOKIES:FALSE/'  \
    /etc/lynx.cfg
cd
exit 0
```

9.15 CA-Certificates

CA-Certificates are used for https web pages.

```
su - ca-certificates
# 1 minute
# Inspired from
# http://linuxfromscratch.org/blfs/view/stable/postlfs/cacerts.html

cp /download/certdata.txt /build
cd /build

cat > /bin/make-cert.pl << 'EOF'
#!/bin/perl -w

# Used to generate PEM encoded files from Mozilla certdata.txt.
# Run as ./make-cert.pl > certificate.crt
#
# Parts of this script courtesy of RedHat (mkcabundle.pl)
#
# This script modified for use with single file data (tempfile.cer)
# extracted from certdata.txt, taken from the latest version in the
# Mozilla NSS source.
# mozilla/security/nss/lib/ckfw/builtins/certdata.txt
#
# Authors: DJ Lucas
#          Bruce Dubbs
#
```

```
# Version 20120211

my $certdata = './tempfile.cer';

open( IN, "cat $certdata|" )
    || die "could not open $certdata";

my $incert = 0;

while ( <IN> )
{
    if ( /^CKA_VALUE MULTILINE_OCTAL/ )
    {
        $incert = 1;
        open( OUT, "|openssl x509 -text -inform DER -fingerprint" )
            || die "could not pipe to openssl x509";
    }

    elsif ( /^END/ && $incert )
    {
        close( OUT );
        $incert = 0;
        print "\n\n";
    }

    elsif ($incert)
    {
        my @bs = split( /\\/ );
        foreach my $b (@bs)
        {
            chomp $b;
            printf( OUT "%c", oct($b) ) unless $b eq '';
        }
    }
}
EOF

chmod +x /bin/make-cert.pl



cat > /bin/make-ca.sh << 'EOF'
#!/bin/sh
# Begin make-ca.sh
# Script to populate OpenSSL's CApath from a bundle of PEM formatted
# CAs
#
# The file certdata.txt must exist in the local directory
# Version number is obtained from the version of the data.
#
# Authors: DJ Lucas
#          Bruce Dubbs
```

```
#
# Version 20120211

certdata="certdata.txt"

if [ ! -r $certdata ]; then
  echo "$certdata must be in the local directory"
  exit 1
fi

REVISION=$(grep CVS_ID $certdata | cut -f4 -d'$')

if [ -z "${REVISION}" ]; then
  echo "$certfile has no 'Revision' in CVS_ID"
  exit 1
fi

VERSION=$(echo $REVISION | cut -f2 -d" ")

TEMPDIR=$(mktemp -d)
TRUSTATTRIBUTES="CKA_TRUST_SERVER_AUTH"
BUNDLE="BLFS-ca-bundle-${VERSION}.crt"
CONVERTSCRIPT="/bin/make-cert.pl"
SSLDIR="/etc/ssl"

mkdir "${TEMPDIR}/certs"

# Get a list of starting lines for each cert
CERTBEGINLIST=$(grep -n "^# Certificate" "${certdata}" | cut -d ":" -f1)

# Get a list of ending lines for each cert
CERTENDLIST=$(grep -n "^CKA_TRUST_STEP_UP_APPROVED" "${certdata}" \
    | cut -d ":" -f 1)

# Start a loop
for certbegin in ${CERTBEGINLIST}; do
  for certend in ${CERTENDLIST}; do
    if test "${certend}" -gt "${certbegin}"; then
      break
    fi
  done

  # Dump to a temp file with the name of the file as the beginning
  # line number
  sed -n "${certbegin},${certend}p" "${certdata}" \
      > "${TEMPDIR}/certs/${certbegin}.tmp"
done

unset CERTBEGINLIST CERTDATA CERTENDLIST certbegin certend

mkdir -p certs
rm -f certs/*      # Make sure the directory is clean
```

```
for tempfile in ${TEMPDIR}/certs/*.tmp; do
  # Make sure that the cert is trusted...
  grep "CKA_TRUST_SERVER_AUTH" "${tempfile}" | \
    egrep "TRUST_UNKNOWN|NOT_TRUSTED" > /dev/null

  if test "${?}" = "0"; then
    # Throw a meaningful error and remove the file
    cp "${tempfile}" tempfile.cer
    perl ${CONVERTSCRIPT} > tempfile.crt
    keyhash=$(openssl x509 -noout -in tempfile.crt -hash)
    echo "Certificate ${keyhash} is not trusted!  Removing..."
    rm -f tempfile.cer tempfile.crt "${tempfile}"
    continue
  fi

  # If execution made it to here in the loop, the temp cert is trusted
  # Find the cert data and generate a cert file for it

  cp "${tempfile}" tempfile.cer
  perl ${CONVERTSCRIPT} > tempfile.crt
  keyhash=$(openssl x509 -noout -in tempfile.crt -hash)
  mv tempfile.crt "certs/${keyhash}.pem"
  rm -f tempfile.cer "${tempfile}"
  echo "Created ${keyhash}.pem"
done

# Remove blacklisted files
# MD5 Collision Proof of Concept CA
if test -f certs/8f111d69.pem; then
  echo "Certificate 8f111d69 is not trusted!  Removing..."
  rm -f certs/8f111d69.pem
fi

# Finally, generate the bundle and clean up.
cat certs/*.pem >  ${BUNDLE}
rm -r "${TEMPDIR}"
EOF

chmod +x /bin/make-ca.sh



cat > /bin/remove-expired-certs.sh << 'EOF'
#!/bin/sh
# Begin /bin/remove-expired-certs.sh
#
# Version 20120211

# Make sure the date is parsed correctly on all systems
mydate()
{
```

```
  local y=$( echo $1 | cut -d" " -f4 )
  local M=$( echo $1 | cut -d" " -f1 )
  local d=$( echo $1 | cut -d" " -f2 )
  local m

  if [ ${d} -lt 10 ]; then d="0${d}"; fi

  case $M in
    Jan) m="01";;
    Feb) m="02";;
    Mar) m="03";;
    Apr) m="04";;
    May) m="05";;
    Jun) m="06";;
    Jul) m="07";;
    Aug) m="08";;
    Sep) m="09";;
    Oct) m="10";;
    Nov) m="11";;
    Dec) m="12";;
  esac

  certdate="${y}${m}${d}"
}

OPENSSL=/bin/openssl
DIR=/etc/ssl/certs

if [ $# -gt 0 ]; then
  DIR="$1"
fi

certs=$( find ${DIR} -type f -name "*.pem" -o -name "*.crt" )
today=$( date +%Y%m%d )

for cert in $certs; do
  notafter=$( $OPENSSL x509 -enddate -in "${cert}" -noout )
  date=$( echo ${notafter} |  sed 's/^notAfter=//' )
  mydate "$date"

  if [ ${certdate} -lt ${today} ]; then
     echo "${cert} expired on ${certdate}! Removing..."
     rm -f "${cert}"
  fi
done
EOF

chmod +x /bin/remove-expired-certs.sh


make-ca.sh
remove-expired-certs.sh certs
```

```
install -d /etc/ssl/certs
cp -v certs/*.pem /etc/ssl/certs
c_rehash
install BLFS-ca-bundle*.crt /etc/ssl/ca-bundle.crt
ln -sfv ../ca-bundle.crt /etc/ssl/certs/ca-certificates.crt

rm BLFS-ca-bundle*.crt
rm certdata.txt
rm -rf certs

cd
exit 0
```

9.16 Procps-ng

The procps-ng package contains utilities that give information about processes using the `/proc` filesystem. The package includes the commands `ps`, `top`, `vmstat`, `w`, `kill`, `free`, `slabtop`, and `skill`.

```
su - procps-ng
# 1 minute
tar xf /download/procps-ng-3.3.0.tar.gz -C /build
cd /build/procps-ng-3.3.0

# From http://lists.gnu.org/archive/html/bug-make/2010-07/msg00153.html
# ps/proc.mk makefile uses LIBPROC, which is set in proc/module.mk:
#sed '177s,\*/module.mk,proc/module.mk ps/proc.mk,' -i.orig Makefile

./configure --prefix=
make
make install
cd ..
rm -rf procps-ng-3.3.0
cd
exit 0
```

Option `lib64=lib` makes the directory `/lib` the one where to put 64 bit libraries, default would be `/lib64`.

Option `ldconfig=` is used in order not to use current host's `ldconfig`.

Option `install="install -D"` is used so that all the files installed are owned by the current user. By default, all installed files are owned by root.

9.17 Package Users Final Tweaks

In order to simplify the build of future packages, create the following file:

```
cat > /etc/pkgusr/skel-package/build-me.sh << EOF
# Exit on error:
set -e

wget
tar xf
```

```
cd
./configure --prefix=
make install
cd ..
rm -rf
rm

exit 0
EOF

chmod u+x /etc/pkgusr/skel-package/build-me.sh
```

Then:

```
cat >> /etc/pkgusr/bash_profile << 'EOF'
if [[ -f build-me.sh ]]
    then mv build-me.sh build-`whoami`.sh
    if [[ -f /src/recipes-1.9.x/`whoami` ]]
        then cp /src/recipes-1.9.x/`whoami` build-`whoami`.sh
    elif [[ -f /src/recipes-1.8/`whoami` ]]
        then cp /src/recipes-1.8/`whoami` build-`whoami`.sh
    elif [[ -f /src/recipes-1.7/`whoami` ]]
        then cp /src/recipes-1.7/`whoami` build-`whoami`.sh
    elif [[ -f /src/recipes-1.6/`whoami` ]]
        then cp /src/recipes-1.6/`whoami` build-`whoami`.sh
    elif [[ -f /src/recipes-1.5/`whoami` ]]
        then cp /src/recipes-1.5/`whoami` build-`whoami`.sh
    fi
fi
EOF
```

Because i wrote many recipes in the past, you can use them when possible in order to extend your OS. Connect to the wired internet first:

```
ifconfig eth0 up
dhcpcd eth0
```

Now download my recipes:

```
#mkdir -v /src/recipes-1.{5,6,7,8,9.x}
mv /src/recipes-1.9.{0,x}

cd /src/recipes-1.5
wget -N http://cjarry.org/gnu-linux/gllfsc/recipes/gllfsc-1.0-to-1.5/0-recipes-1.5
sed -i 's/wget h/wget -N h/' 0-recipes-1.5
chmod u+x 0-recipes-1.5
./0-recipes-1.5

cd /src/recipes-1.6
wget -N http://cjarry.org/gnu-linux/gllfsc/recipes/gllfsc-1.6/0-recipes-1.6
sed -i 's/wget h/wget -N h/' 0-recipes-1.6
chmod u+x 0-recipes-1.6
./0-recipes-1.6

cd /src/recipes-1.7
wget -N http://cjarry.org/gnu-linux/gllfsc/recipes/gllfsc-1.7/0-recipes-1.7
```

```
sed -i 's/wget h/wget -N h/' 0-recipes-1.7
chmod u+x 0-recipes-1.7
./0-recipes-1.7

cd /src/recipes-1.8
wget -N http://cjarry.org/gnu-linux/gllfsc/recipes/gllfsc-1.8/0-recipes-1.8
sed -i 's/wget h/wget -N h/' 0-recipes-1.8
chmod u+x 0-recipes-1.8
./0-recipes-1.8

cd /src/recipes-1.9.x
wget -N http://cjarry.org/gnu-linux/gllfsc/recipes/gllfsc-1.9.x/0-recipes-1.9.x
sed -i 's/wget h/wget -N h/' 0-recipes-1.9.x
chmod u+x 0-recipes-1.9.x
./0-recipes-1.9.x
cd
```

9.18 Archiving the Complete System

```
# Clean up:
#rm /src/*
rm /root/*
rm /root/.bash_history
rm -rf /share/doc
#mv /share/man/man* /share
#rm -rf /share/man/*
#mv /share/man[1-8] /share/man

# Strip binaries
# 141 MB before, 44 MB after
strip --strip-all /bin/*
```

Switch to another operating system on the same machine, for instance GLLFSC 1.9.0. Then issue the following command:

```
# To be done outside GLLFSC:
# 4 minutes
tar -cjf gllfsc-core2-1.9.1-completed.tar.bz2 \
    bin boot dev etc home include lib* local man mnt opt proc root run \
    sbin service share src static sys tmp usr var
```

9.19 Add User

To create a new user, without root rights:

```
useradd -m USER
```

This will create a new user named '`USER`' with group '`USER`' and user's home at `/home/USER`.

To give a password to this user:

```
passwd USER
```

You may want to change the color of this user's prompt:

```
cat > /home/USER/.bash_profile << EOF
export PS1='\[\e[32m\]\A-\W\[\e[00m\]$ '
EOF
chown USER:USER /home/USER/.bash_profile
```

9.20 Halting the Computer

In order to halt the computer after this build process, type:

```
init.sysv 0
```

If you prefer to reboot instead type:

```
init.sysv 6
```

The next time you use GLLFSC, runit will be the default init system and you will have to type '`init 0`' to halt the operating system and '`init 6`' to reboot.

10 Further Readings

On my personal website at `http://cjarry.org/gnu-linux/gllfsc/gllfsc.en.html`, there is some information on how to connect to the internet with wifi, and how to extend GLLFSC, for instance instructions on how to build Xorg, chose a font and a web browser, text-based or graphical.

Haiyong Sun's website (in Chinese): `http://blog.chinaunix.net/uid/436750.html`. It includes documents on building a GNU/Linux system for Loongson and a GNU/Hurd system for x86. He also owns repositories on `https://github.com/sunhaiyong1978/`, some of which concern the LoongArch architecture.

The suckless team[1] is a group of programmers that share the following philosophy[2]:

> Focus on simplicity, clarity and frugality. Our philosophy is about keeping things simple, minimal and usable. We believe this should become the mainstream philosophy in the IT sector. Unfortunately, the tendency for complex, error-prone and slow software seems to be prevalent in the present-day software industry. We intend to prove the opposite with our software projects.

The simple and lightweight programs released by this team are interesting for everyone who like small, reactive and reliable programs.

Musl[3] is a free software C library for the kernel Linux. It is simple and suitable for both static and dynamic linking of binaries.

[1] `http://suckless.org`

[2] `http://suckless.org/philosophy/`

[3] `https://musl.libc.org/`

11 Thanks

I am particularily grateful to Haiyong Sun for having shared his knowledge on building a free operating system for Loongson 2F machines, this document was heavily based on his work.

Appendix A GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
`https://fsf.org/`

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The "publisher" means any person or entity that distributes copies of the Document to the public.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

   You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

   You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

   If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both

covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its

Title Page, then add an item describing the Modified Version as stated in the previous sentence.

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.

O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements."

6. COLLECTIONS OF DOCUMENTS

   You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

   You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

   A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

   If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

   Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

   If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

   You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

   However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

   Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See `https://www.gnu.org/licenses/`.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A "Massive Multiauthor Collaboration" (or "MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

"CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

"Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is "eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with. . . Texts." line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Appendix B GNU General Public License

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. https://fsf.org/

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program—to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

   "This License" refers to version 3 of the GNU General Public License.

   "Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

   "The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

   To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

   A "covered work" means either the unmodified Program or a work based on the Program.

   To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

   To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

   An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

   The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

   A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

   The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

   The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

   All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

   You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

   Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

   No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

   When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

   You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

   You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

   You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

   a. The work must carry prominent notices stating that you modified it, and giving a relevant date.
   b. The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
   c. You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable

section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d. If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b. Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c. Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d. Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e. Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything

designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

a. Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

b. Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c. Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d. Limiting the use for publicity purposes of names of licensors or authors of the material; or

e. Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f. Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

    Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

    An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

    You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

    A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

    A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

    Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

    In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

    If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

    If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

    If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

    Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

    The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

    Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

    If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

    Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

    THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRIT-

ING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

    IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

    If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
one line to give the program's name and a brief idea of what it does.
Copyright (C) year name of author

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or (at
your option) any later version.

This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program.  If not, see https://www.gnu.org/licenses/.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
program Copyright (C) year name of author
```

```
This program comes with ABSOLUTELY NO WARRANTY; for details type ‘show w’.
This is free software, and you are welcome to redistribute it
under certain conditions; type ‘show c’ for details.
```

The hypothetical commands ‘`show w`’ and ‘`show c`’ should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an “about box”.

You should also get your employer (if you work as a programmer) or school, if any, to sign a “copyright disclaimer” for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see `https://www.gnu.org/licenses/`.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read `https://www.gnu.org/licenses/why-not-lgpl.html`.